

**JOINT WMO-IOC TECHNICAL COMMISSION
FOR OCEANOGRAPHY AND MARINE
METEOROLOGY (JCOMM)**

FOURTH SESSION

Yeosu, Republic of Korea,
23 to 31 May 2012

Submitted by:

Date:

Original Language:

Agenda Items:

JCOMM-4/BM. 10

WMO Secretary-General
and UNESCO/IOC
Executive Secretary

18.04.2012

English

10

**REVIEW OF TECHNICAL REGULATIONS OF INTEREST TO THE COMMISSION,
INCLUDING GUIDES AND OTHER TECHNICAL PUBLICATIONS**

BACKGROUND MATERIAL

SUMMARY

Reference: JCOMM-4/Doc. 10

CONTENT OF DOCUMENT:

Appendices:

Background information on changes Proposed to WMO Nos. 558, 471, and 47

The changes proposed by JCOMM Expert Teams to WMO Publications Nos. 558, 471, and 47 are detailed below in track changes (for Nos. 558 and 471), and with background information (for No. 47).

These correspond exactly to the changes proposed in JCOMM-IV Doc. 10.

BACKGROUND MATERIAL

1) MODIFICATIONS PROPOSED TO THE MANUAL ON MARINE METEOROLOGICAL SERVICES – WMO NO. 558

Note: The changes proposed by the ETMC to WMO No. 558 appear in track changes below.

5. MARINE CLIMATOLOGICAL SUMMARIES SCHEME

NOTE: The international arrangements regarding the Marine Climatological Summaries Scheme are based on Resolution 35 (Cg-IV), Recommendation 36 (68-CMM), Recommendation 6 (CMM-VI), Recommendation 15 (CMM-VII), Recommendation 35 (79-CMM), Recommendation 6 (CMM-VIII), Recommendation 8 (CMM-VIII), Recommendation 12 (CMM-X) and Recommendation 11 (CMM-XI), Recommendation 8 (JCOMM-I), Recommendation 9 (JCOMM-II), Recommendation 9 (JCOMM-III), Recommendation 12 (JCOMM-III).

5.1 Principles

The principles of the Marine Climatological Summaries Scheme are as follows:

Principle 1

The oceans and seas are divided into eight areas of responsibility for the purpose of preparing marine climatological summaries and with a view to continued international co-operation regarding the collection, archiving and exchange of marine data.

Principle 2

Members having assumed responsibility for the respective areas as shown in Appendix I.5 — hereinafter called Responsible Members — should optionally prepare climatological summaries for their area of responsibility. The preferred method of producing summaries is the chart form. However, Members may prepare, without cost to the World Meteorological Organization, climatological summaries in tabular form for selected representative areas. The tabular form of the summaries is to be used for historical fixed ship stations. The procedures are specified in paragraph 5.3.

Principle 3

Two Responsible Members operate global collecting centres as shown in Appendix I.6. Members once operating (historical) fixed ship stations; or selected, supplementary and auxiliary ship stations; make available all surface observations from these stations to both global collecting centres in accordance with the procedures specified in the agreed plan. The cost of this work is borne by the Member operating the ship stations.

Principle 4

Global collecting centres ensure that minimum quality control has been applied to the data, and exchange the data collected with each other, to ensure that both have a complete data set. Global collecting centres ensure that one copy of the global (update) data is sent quarterly to those Responsible Members which wish to maintain a global data set — otherwise a data set for their area of responsibility is sent to the remaining Responsible Members. The cost of this work is borne by the Members operating the global collecting centres.

Principle 5

Responsible Members make available, on request, copies of marine climatological data in the agreed international exchange format (IMMT). The Member making the request may be asked to bear the cost of copying the data. Other formats may be agreed between the requesting Member and the Responsible Member provided that the requesting Member undertakes to bear the additional expenditure involved.

5.2 Areas of responsibility

Each Responsible Member should optionally prepare climatological summaries of observations made

after 1960 in accordance with the agreed plan (Appendix I.8), in chart form for its area of responsibility, in tabular form for a number of selected representative areas in its area of

responsibility, or in tabular form for a number of (historical) fixed ship stations within its area and for fixed ship stations once operated solely by the Responsible Member in the area of another Responsible Member.

5.2.1 Boundaries of areas of responsibility

5.2.1.1 The areas of responsibility shall be as given in Appendix I.5.

5.2.1.2 Examination of the boundaries of areas of responsibility with a view to making recommendations for adjustment shall be the responsibility of the Joint WMO-IOC Technical Commission for Oceanography and Marine Meteorology (JCOMM). Such adjustments may become necessary if other Members wish to become Responsible Members. Alternatively, existing Responsible Members may find that it is necessary to adjust boundaries.

5.2.1.3 Adjustments of boundaries of areas of responsibility should be kept to a minimum.

5.2.2 Polar and extra-polar regions

For the purpose of marine climatological summaries, polar regions are defined as extending poleward from latitudes 60°N and 50°S, respectively.

5.2.3 Selected representative areas

NOTE: This section applies only if the tabular form of summaries is produced.

5.2.3.1 Each Responsible Member shall propose a number of selected representative areas from within its assigned area of responsibility. These areas should be chosen to achieve a good density of data or because of other requirements, such as climatic gradients and related factors.

5.2.3.2 Responsible Members shall submit the list of areas selected to the president of JCOMM who will ensure that the final choice of the selected representative areas, proposed by the Responsible Members, provides a reasonable distribution throughout all areas of responsibility.

5.2.3.3 The indices system, which is given in Appendix I.7 shall be used to code the extent and location of the selected representative areas.

5.2.3.4 The selected representative areas shall remain fixed in their size, shape and position for as many years as possible.

NOTE: The recommended maximum size of a selected area in polar regions is 50 one-degree squares.

5.2.3.5 A map (or maps) showing the distribution of the selected representative areas in each area of responsibility should be included in the summaries for that area.

5.2.4 Fixed ship station area/ocean island stations/moored buoys and fixed platforms

5.2.4.1 The "on station" area should be defined for each fixed station. This area should consist of the smallest number of adjacent one-degree squares, centred on the nominal fixed position, which contain at least 95 per cent of the observations from the fixed station.

5.2.4.2 It should be left to the discretion of the Responsible Members to publish data from ocean island stations located in data-sparse areas as supplements to the marine climatological summaries. The island data summaries should not be combined with summaries of ocean data and a warning to this effect must be included in the supplements. Data from ocean island stations should be published in the same form as for fixed ship stations.

5.3 Procedures for preparing marine climatological summaries

5.3.1 General plan

The plan for the production of marine climatological summaries is shown in Appendix I.8.

5.3.2 Layout of marine climatological summaries

5.3.2.1 CHART FORM

The layout of the marine climatological summary in chart form is given in Appendix I.9.

5.3.2.2 TABULAR FORM

The parameters to be included in the tabular form of marine climatological summaries are given in Appendices I.10, I.11 and I.12.

5.3.3 *Period of marine climatological summaries*

5.3.3.1 ANNUAL SUMMARIES

The routine publication of annual summaries ceased in 1981 (Recommendation 6 (CMM-VIII)). However, annual climatological summaries may be published by the Responsible Members on an optional basis, preferably in chart form. The processing of data shall be continued so that the original observations will be readily available upon request.

5.3.3.2 DECADAL SUMMARIES

Decadal climatological summaries should be prepared for the periods 1961–70, 1971–80, 1981–90, 1991–2000, 2001–2010. The routine production of decadal summaries ceased in 2012. However, such summaries may continue to be published by Responsible Members on an optional basis.

5.4 *Minimum number of observations for the preparation of the marine climatological summaries*

5.4.1 *General*

All available data shall be used in the preparation of annual and decadal summaries.

5.4.2 *Annual summaries*

5.4.2.1 The annual mean for any unit area or selected representative area should not be calculated if there are less than 10 observations from the area in any individual month.

5.4.2.2 Statistics for chart areas and frequency tables should not be prepared if there are less than 10 observations from a unit area of a chart or selected representative area or tabulation in any individual month.

5.4.2.3 For tabular summaries, the data should be listed if there are less than 40 observations from a selected representative area in any individual month and those observations have been made on less than 10 different days of the month.

5.4.2.4 For tabular summaries, the data should be summarized if there are less than 40 observations from a selected representative area in any individual month and those observations have been made on 10 or more different days of the month.

5.4.2.5 The data should be summarized in charts or tabulations if there are less than 40 observations from a selected representative area in any individual month.

5.4.3 *Decadal summaries*

5.4.3.1 Summaries are prepared for decadal periods and not for individual years if there are less than 40 observations from a selected representative area in any individual month.

5.4.3.2 In preparing a climatological summary for a decade or longer period, the summary for each month should be prepared by combining all available observations from that particular months for all years during the period of the summary.

5.4.3.3 It must be clearly stated in the text of the summary when data are summarized, which are known to be irregularly distributed over the 10-year period.

5.5 *Parameters to be included in, and form of, the marine climatological summaries*

5.5.1 *Fixed stations*

Annual and decadal summaries for fixed stations shall be produced in tabular form and shall contain the parameters listed in Appendix I.10.

5.5.2 *Polar and extra-polar regions*

5.5.2.1 ANNUAL SUMMARIES

Data for annual summaries shall be prepared either in a format suitable for publication of charts or alternatively in a format suitable for publication of tables. The type of output required in any individual year is specified in Appendix I.8.

5.5.2.2 DECADAL SUMMARIES

Decadal summaries shall be published either in chart form (preferred) or in tabular form as also indicated in Appendix I.8.

5.5.2.3 CHART FORM

Parameters to be included in the summaries which are produced in chart form are listed in Appendix I.9.

5.5.2.4 TABULAR FORM

Parameters to be included in the summaries are listed in Appendices I.10, I.11 and I.12.

5.5.3 *Inventory of marine climatological summaries*

During the first quarter of each year, Responsible Members should send a list of marine climatological summaries which have been produced during the previous year to the Secretary-General.

5.6 Marine climatological data

5.6.1 *Collection and exchange of data*

5.6.1.1 Members operating (historical) fixed ship stations; or selected, supplementary and auxiliary ship stations; should transfer all surface observations from these stations onto magnetic tape (or other alternative modern media). It is recommended that the data be arranged in the agreed format of the International Maritime Meteorological Tape (IMMT) as described in Appendix I.13. The data should be dispatched to both global collecting centres at three-monthly intervals.

5.6.1.2 The Member originating the data should notify the global collecting centres of the dispatch of the quarterly collection of data. The notification should contain details of the order in which the records are sorted.

5.6.1.3 Members may use the alternative format for maritime meteorological data which is given in Appendix I.14. Use of this or any other alternative format must only be used by mutual agreement between the two Members which are exchanging data.

5.6.1.4 Members should ensure that magnetic tapes (or other modernized computer media) are readable at the global collecting centres..

5.6.1.5 The Responsible Member should indicate clearly, in the summary, the extent to which auxiliary ship data have been used.

5.6.2 *Inventory of marine climatological data*

Global collection centres shall keep an inventory of all marine climatological data received from Members.

5.6.3 *Quality control of data*

5.6.3.1 All Members should make every effort to apply the minimum quality control procedures in Appendix I.15 before dispatching the data to the global collecting centres. These centres should ensure that this minimum quality control has been applied before making the data available to Responsible Members.

5.6.3.2 Quality control of marine data by Members and Responsible Members should be continued and improved. Details of national quality control schemes should be made available to Responsible Members.

5.6.4 *Period before 1961*

5.6.4.1 While the Historical Sea Surface Temperature Data (HSSTD) project provided in the past for the collection and summarizing of marine climatological data for the period 1861 to 1960, this responsibility in the future will be transitioned to modernized international archives (CMOCs – ICOADS). The past participants in the HSSTD project agreed to exchange any additional digitized historical data as they become available.

5.6.4.2 Members having historical data, which are not yet included in the previous HSSTD project (or modern day CMOC), should send those data to the appropriate participating Member. The data

should be converted into the international exchange format (IMMT), or a mutually agreed format, before dispatch to the participating Member. The cost of conversion should be borne by the Member supplying the data.

6. SPECIAL MARINE CLIMATOLOGICAL INFORMATION

6.1 Principles

The principles for collection, storage and processing of special marine climatological information are as follows:

Principle 1

International co-operative arrangements for the collection of special observations from mobile ship stations, i.e. other than those which comprise the Marine Climatological Summaries Scheme, as well as for their storage and eventual processing, include the designation of preferably one international centre suitably equipped for marine data storage and retrieval functions.

Principle 2

In order to ensure the combined use of stored ocean data obtained from special observations at mobile ship stations on the one hand and similar data obtained from measurements at oceanographic stations on the other, arrangements for the ultimate archiving of relevant data include the WMO-IOC Centres for Marine-meteorological and Oceanographic Climate Data (CMOCs), and the ICSU World Data System.

6.2 Procedures

6.2.1 Report of freak waves

NOTES: (1) A freak wave may be defined as a wave of very considerable height ahead of which there is no deep trough. Thus, it is the unusual steepness of the wave which is its outstanding feature and which makes it dangerous to shipping. Reports so far available suggest that such waves have usually occurred where a strong current flows in the opposite direction to a heavy sea and especially when it occurs near the edge of the continental shelf.

(2) International procedures are based on Recommendation 22 (**75-CMM**).

6.2.1.1 Members operating fixed ship stations or selected, supplementary and auxiliary ship stations should encourage marine observers to enter in meteorological log-books detailed information on freak waves, including a full description of the phenomenon (indicating height and horizontal distance between crest and trough, if possible), weather conditions, state of the sea and any other factors which may have influenced the state of the sea, as well as any damage sustained by the ship.

NOTE: A layout of a freak-wave report is contained in Annex II-1.B to the *Guide to Marine Meteorological Services* (WMO-No. 471).

6.2.1.2 When received, freak-wave reports should be sent to the Member which has assumed the responsibility for accepting reports from Members on freak waves, for publishing reports of special interest and for analysing the data in due time and publishing the results.

7. PROVISION OF MARINE METEOROLOGICAL INFORMATION AND EXPERT ADVICE

7.1 Principles

7.1.1 The principle for the provision of marine meteorological information and expert advice is as follows:

Principle

One of the important purposes for which marine meteorological data are preserved is their use in special applications in activities such as engineering design studies, planning of marine operations, expertise in insurance claims or official investigations regarding marine accidents, cargo ventilation studies, etc.

7.2 Procedures

7.2.1 The provision of marine meteorological and related oceanographic information and expert advice on the use and interpretation of data should be arranged according to national practices.

7.2.2 Marine meteorological data should be preserved by Members in a form which renders these data easily accessible for use in applications requiring expert advice.


7.2.3 Members should assist each other in questions requiring marine meteorological expert advice by providing, as far as possible, the requested information in a convenient form.

7.2.4 Supply of marine meteorological data for special application purposes should be governed by the provisions on exchanges of climatological data contained in Chapter [B.1.]3 of Volume 1 of the WMO *Technical Regulations* (WMO-No. 49).

**EXCERPTS FROM THE EXTRACT FROM THE
MANUAL ON MARINE METEOROLOGICAL SERVICES (WMO-NO. 558)**

APPENDIX I.7

**AREAS OF RESPONSIBILITY AND RESPONSIBLE MEMBERS FOR MARINE
CLIMATOLOGICAL SUMMARIES**



Note: The Russian Federation is responsible for the compilation of a complete dataset and the preparation of the summaries for sea areas south of 50°S.

APPENDIX I.8


GLOBAL COLLECTING CENTRES FOR MARINE CLIMATOLOGICAL SUMMARIES
SCHEME

GCC Germany
Deutscher Wetterdienst
P.O. Box 30 11 90
20304 Hamburg
GERMANY
Tel.: +49 40 6690 1444
Fax.: +49 40 6690 1499
Email: gcc@dwd.de
Website: <http://www.dwd.de/gcc>

GCC United Kingdom
Met Office
Saughton House
Broomhouse Drive
Edinburgh, EH11 3XQ
SCOTLAND, UNITED KINGDOM
Tel.: +44 131 528 7313
Fax.: +44 131 528 7345
Email: gcc@metoffice.gov.uk
Website:
http://www.metoffice.gov.uk/weather/marine/observations/gathering_data/gcc.html

APPENDIX I.9

AREA INDICES SYSTEM FOR MARINE CLIMATOLOGICAL SUMMARIES



Representative area	A	shall be coded	:	00037
"	B	"	:	01288
"	C	"	:	51281
"	D	"	:	81288
"	E	"	:	80187
"	F	"	:	31149

The following area indices systems shall be used:

- (a) A selected representative area shall be indicated with reference to the position in the area of the 1-degree square corner which is nearest (1) to the Equator and (2) to the Greenwich meridian, in that sequence;
- (b) A five-figure code shall be used for "area index";
- (c) The first figures of the code - QL_aL_o - shall indicate the 10-degree square in which this 1-degree square is situated, where:
 - (i) The first figure shall be octant (code 3300);
 - (ii) The second figure shall be tens of the latitude of the 10-degree square;
 - (iii) The third figure shall be the tens of the longitude of the 10-degree square.
- (d) The fourth and fifth figures of the code shall be the number of the 1-degree square within the 10-degree square as indicated in the above figure.

APPENDIX I.10

PLAN FOR THE PRODUCTION OF MARINE CLIMATOLOGICAL SUMMARIES OVER THE PERIOD 1961-2020

Period	FIXED STATIONS ^a	REPRESENTATIVE AREA/AREA OF RESPONSIBILITY ^b		
	Tables ^c	Tables ^c	Charts ^{b,d}	Isopleths ^{b,d,e}
1961-1970, annual decadal	X, X	X, O ^g	O ^f , O ^g	O, O
1971-1980, annual decadal	O, X	O, O ^g	O ^f , O ^g	O, O
1981-1990, annual decadal	O, X	O, O ^g	O, O ^g	O, O
1991 – 2000, annual, decadal	O, X	O, O ^g	O, O ^g	O, O
2001 – 2010 annual, decadal	O, X	O, O ^g	O, O ^g	O, O
2011 – 2020, annual, decadal	O, X	O, O ^g	O, O ^g	O, O

KEY: X - Recommended
O - Optional

NOTES: *a* - Ocean weather stations and other fixed stations
b - Total area of responsibility
c - Summary tables (existing regulations)
d - Numerical data on charts of sea areas (marine climatological summary charts)
e - In addition to charts
f - Recommended instead of tables for Responsible Members who have not yet published annual summaries
g - Published in chart or tabular form or both at the option of Responsible Members

APPENDIX I.11

LAYOUT FOR MARINE CLIMATOLOGICAL SUMMARY CHARTS FOR REPRESENTATIVE AREAS

1. General


For each area of responsibility charts will be prepared in accordance with the following specifications.

2. Projection

The recommended projection for all areas except the polar regions is the Mercator projection. For the polar regions the polar stereographic projection is recommended. Where charts are produced by typewriter or line-printer systems other projections may be used.

3. Unit areas

Data will be plotted on unit areas, preferably rectangular, as shown below (**Figure not complete**):



Data 1-3 are specified according to the element summarized

4. Dimensions of the unit areas

The unit areas containing relevant numerical data should, as far as possible, have a uniform size. In data-sparse regions unit areas as large as $5^\circ \times 10^\circ$ may be necessary; for most parts of the oceans $5^\circ \times 5^\circ$ squares will be suitable. In the vicinity of coasts or in semi-enclosed seas $2^\circ \times 2^\circ$ or even $1^\circ \times 1^\circ$ squares may be appropriate. The selection of unit areas will be undertaken by each Responsible Member and will be a compromise between the available number of observations and the expected climatic gradients. The unit areas, once chosen, should be retained in all subsequent annual and decadal charts.

5. Specification of elements to be presented on summary charts:

Chart	Data	Element (resolution/unit)
I	1	Mean air temperature (T , 0.1°C)
	2	Standard deviation of air temperature ¹ (σ_T , 0.1°C)
	3	Number of observations of air temperature (N_T)
II	1	Mean sea-surface temperature (T_W , 0.1°)
	2	$\sigma_{TW}(0.1^\circ\text{C})$
	3	N_{Td}
Chart	Data	Element (resolution/unit)
	1	Mean dew-point temperature (T_d , 0.1°C)

III	2	σ_{Td} (0.1°C)
	3	N_{Td}
IV	1	Mean air-sea temperature difference ($T-T_w$) (ΔT , 0.1°C)
	2	$\sigma_{\Delta T}$ (0.1°C)
	3	$N_{\Delta T}$
V	1	Mean sea-level pressure (P, 0.1 hPa)
	2	σ_p (0.1 hPa)
	3	N_p
VI	1	Median wind speed (f_{50} , 0.1 m s ⁻¹)
	2	Standard deviation of wind speed (σ_f , 0.1 m s ⁻¹)
	3	Steadiness of wind ²
VII	1	Prevailing wind direction ³
	2	Number of wind-speed observations (N_f)
	3	Number of measured wind-speed observations
VIII	1	% of light winds (≤ 3 m s ⁻¹ , \leq Beaufort 2) (0.1%)
	2	% of strong winds (≥ 11 m s ⁻¹ , \geq Beaufort 6) (0.1%)
	3	Prevailing direction ³ of strong winds (1°)
IX	1	% gales (≥ 17 m s ⁻¹ , \geq Beaufort 8) (0.1%)
	2	Prevailing direction ³ of gales (1°)
	3	—
X	1	Median wave height ⁴ (H_{50} , 0.5 m)
	2	σ_H (0.1m)
	3	N_H
XI	1	% waves ≤ 1.5 m (0.1%)
	2	% waves ≥ 4 m (0.1%)
	3	% waves ≥ 6 m (0.1%)
XII	1	% wave periods ⁴ ≥ 6 s (1 s)
	2	Prevailing swell direction ³ (1°)
	3	Number of swell observations
XIII	1	% observations with rain or drizzle ⁵ (0.1%)
	2	% observations with other forms of precipitation ⁶ (0.1%)
	3	Number of present weather observations
XIV	1	% total cloud amount $\leq 2/8$ (0.1%)
	2	% total cloud amount $\leq 6/8$ ⁷ (0.1%)
	3	Number of total cloud observations
XV	1	% visibility < 1 km (VV = 90-93) (0.1%)
	2	% visibility ≥ 10 km (VV = 97-99) (0.1%)
	3	Number of visibility observations
XVI	1	Mean latitude of observations (L_a , 0.1°)
	2	Mean longitude of observations (L_o , 0.1°)
	3	Total number of observations
Chart	Data	Element (resolution/unit)
XVII	1	σ_{La} (0.1°)
	2	σ_{Lo} (0.1°)
	3	Total number of observations
XVIII	1	Number of reports of icing
	2	% potential moderate or severe superstructure icing ⁸ (0.1%)

- 3 Number of observations containing air temperature and wind speed

NOTES: (1) $\sigma = \left\{ \frac{\left[\sum_{i=1}^N x_i - \bar{x} \right]}{N-1} \right\}^{1/2}$ where x is the value of an individual observation.

(2) Steadiness = ratio of speed of the monthly mean vector wind to the speed of the monthly mean scalar wind.

- (3) A resultant vector mean direction with each wind speed or wave height set equal to 1.
 (4) Height of sea or swell.
 (5) (ww = 50-67, 80-82).
 (6) (ww = 68-99 except 80-82, 98).
 (7) N = 6, 7, 8, 9.
 (8) ff $\geq 11 \text{ m s}^{-1}$, TTT $\leq 2^\circ\text{C}$.

6. Production of charts

Monthly and annual charts will be produced as specified above. Mean values and standard deviations are to be computed from the total numbers of observations in all cases (i.e., for the annual charts, the annual means and standard deviations will be computed from the sums of the individual observed values). Parameters for decadal charts will be computed in the same manner.

APPENDIX I.12

PARAMETERS TO BE INCLUDED IN MARINE CLIMATOLOGICAL SUMMARIES FOR
(HISTORICAL) FIXED SHIP STATIONS

Table 1 -Mean position of all observations

This table is not included in summaries for fixed ship stations.

Table 2 -Air temperature

- (a) Monthly means;
- (b) Mean for the year, computed from monthly means;
- (c) Extremes with dates and hours of occurrence and 5, 25, 50, 75 and 95 percentile values for each month;
- (d) Number of observations.

Table 3 -Dew-point temperature

- (a) Monthly means;
- (b) Mean for the year, computed from monthly means;
- (c) Extremes with dates and hours of occurrence and 5, 25, 50, 75 and 95 percentile values for each month;
- (d) Number of observations.

Table 4 -Sea-surface temperature

- (a) Monthly means;
- (b) Mean for the year, computed from monthly means;
- (c) Extremes with dates and hours of occurrence and 5, 25, 50, 75 and 95 percentile values for each month;
- (d) Number of observations.

Table 5 -Air-sea temperature difference

- (a) Monthly means;
- (b) Mean for the year, computed from monthly means;
- (c) Extremes with dates and hours of occurrence and 5, 25, 50, 75 and 95 percentile values for each month;
- (d) Number of observations.

Table 6 -Visibility

- (a) Percentage frequency for each month for each code figure 90-99 inclusive (WMO code table 4377);
- (b) Annual percentage frequency for each code figure 90-99 inclusive;
- (c) Number of days for each month and for the year with VV = 90-93 and/or W = 4;
- (d) Number of observations.

Table 7 -Weather

- (a) Number of days for each month with precipitation, i.e. days when one or more of the ww or W code figures (WMO codes tables 4500 and 4677) listed in subsections (b) to (e) were reported (excluding ww = 17, 98);
- (b) Number of days for each month with rain and/or drizzle (ww = 20, 21, 24, 25, 50-67, 80-82; W = 5, 6, 8);
- (c) Number of days for each month with snow or snow and rain (ww = 22, 23, 26, 68-79, 83-86; W = 7);
- (d) Number of days for each month with hail (ww = 27, 87-90);
- (e) Number of days for each month with thunderstorms (ww = 17, 29, 91-99; W = 9);
- (f) Number of days for each month with:
 - (i) Gales (Beaufort force ≥ 8);
 - (ii) Storms (Beaufort force ≥ 10);
 - (iii) Hurricane force winds (Beaufort force = 12);
- (g) Number of complete observing days for items (a) to (f);
- (h) Total number of days annually for each item (a) to (f);
- (i) Monthly percentage frequency of occurrence of precipitation at the time of observation (ww = 50-97, 99);
- (j) Annual percentage frequency of occurrence of precipitation at the time of observation (ww = 50-97, 99);
- (k) Number of observations for items (i) and (j);
- (l) If measured, monthly and annual amount of precipitation;
- (m) Annual percentage frequency of occurrence of each individual ww code figure 50-97, 99.

NOTE: It is recommended that the number of days with precipitation etc. be obtained by making appropriate entries in the log-book at the end of each day, as shown in the following example:

Precipitation	Rain or drizzle	Snow or rain and snow	Hail	Thunder	Fog	Gale	Storm	Hurricane
---------------	--------------------	-----------------------------	------	---------	-----	------	-------	-----------

√	√		√		√			
---	---	--	---	--	---	--	--	--

In order to facilitate the computation of the monthly and annual totals, these entries can be punched in fixed columns as "1" on a "day-card". If this is done, the sorting of the international maritime punch cards by the various combinations of ww and W is avoided and an accurate total obtained.

Table 8 -Wind direction and speed

- (a) Monthly percentage frequencies for the following ranges of speed:
 - (i) 0 to 4 knots;
 - (ii) 5 to 9 knots;
 - (iii) 10 to 14 knots;
 - (iv) 15 to 19 knots;
 - (v) 20 to 24 knots;
 - (vi) 25 to 29 knots;
 - (vii) 30 to 39 knots;
 - (viii) 40 to 49 knots, etc;
 and for directions by sectors of 30°, true north bisecting the first sector;
- (b) Monthly total of observations for each sector irrespective of speed;
- (c) Monthly percentage frequency of occurrence of observations for each range of speed irrespective of direction;
- (d) Mean monthly wind speed in knots, derived from all wind-speed observations;
- (e) Mean wind speed for the year, computed from monthly means;
- (f) Number of observations corresponding to item (d);
- (g) Highest wind speed for each month and for the year, with dates and hours of occurrence;
- (h) Vector mean wind for each month and its components (W to E and S to N directions taken as positive).

Table 9 -Sea-level pressure

- (a) Monthly means for each hour of observation;
- (b) Monthly means for all hours of observation;
- (c) Mean for the year, computed from monthly means;
- (d) Number of observations;
- (e) Extremes with dates and hours of occurrence and 5, 25, 50, 75 and 95 percentile values for each month.

Table 10 - Cloud

- (a) Monthly mean total amount for each hour of observation;
- (b) Monthly mean for all hours of observation;
- (c) Monthly mean for all hours of observation in respect of low cloud only (defined as cloud for which h is any code figure (WMO code table 1600) from 0 to 8 inclusive);
- (d) Monthly percentage frequency of observations in the following ranges of total cloud amount (all hours of observing combined):
 - (i) 2 oktas or less;
 - (ii) 3 to 5 oktas inclusive;
 - (iii) 6 to 7 oktas;
 - (iv) 8 oktas;
- (e) As item (d), but for low cloud only;
- (f) Percentage frequency of height of low cloud for each month, subdivided into ranges corresponding to WMO code table 1600;
- (g) Same for the year for items (a) to (f) inclusive computed from the monthly means or frequencies;
- (h) Number of observations.

Table 11 - Waves

- (a) Seasonal tables, with the first-mentioned parameter arranged along the vertical, containing:
 - (i) Number of observations of any combination of wave height and period irrespective of direction;
 - (ii) Number of observations of any combination of wave direction and height irrespective of period;
 - (iii) Number of observations of any combination of wave direction and period irrespective of height;
 - (iv) Number of observations of any wave height irrespective of period and direction;
 - (v) Number of observations of any wave period irrespective of height and direction;
 - (vi) Number of observations of any wave direction irrespective of height and period;
 - (vii) Total number of observations;
- (b) The following seasons shall be used:
 - (i) December (of the previous year), January, February, March;
 - (ii) April, May;
 - (iii) June, July, August, September;
 - (iv) October, November;
- (c) Starting with data for 1971, wave data should be provided in sets of three tables: direction versus height, direction versus period and height versus period, with a line or column "undetermined" with respect to wave period and direction, respectively;

NOTE: For the period 1961-1970, data are provided as shown in Figure 1.

- (d) Only waves with greatest height should be selected. If two waves in the same observation have equal height, the one with the largest period should be selected. If the periods are also equal or undetermined, the direction of the second wave reported should be used;
- (e) In ten-year summaries the tables as indicated under (a) to (c) above should be included on a monthly basis and, in addition, for seasonal tables as shown in Figure 1.

*

*

*




Figure 1 – Monthly percentage frequency of wave directions by specified periods and heights

Legend

X* : Period and direction observed, but not wave height.

X₁ : Period and height observed, but not wave direction.

X₂ : Direction and height observed, but not wave period.

N : Number of observations.

APPENDIX I.13

PARAMETERS TO BE INCLUDED IN MARINE CLIMATOLOGICAL SUMMARIES FOR SELECTED REPRESENTATIVE AREAS IN EXTRA-POLAR REGIONS

Table 1 -Mean position of all observations

- (a) Monthly mean position of all observations;
- (b) Mean position for the year as calculated from the monthly mean positions.

Table 2 -Air temperature

- (a) Monthly means;
 - (b) Mean for the year, computed from monthly means;
 - (c) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
 - (d) Monthly and annual total number of observations.
- NOTE: The unused higher and lower ranges need not be printed; all intervals between the extreme annual ranges should be retained.

Table 3 - Dew-point temperature

- (a) Monthly means;
 - (b) Mean for the year, computed from monthly means;
 - (c) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
 - (d) Monthly and annual total number of observations.
- NOTE: See note under Table 2.

Table 4 -Sea-surface temperature

- (a) Monthly means;
 - (b) Mean for the year, computed from monthly means;
 - (c) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
 - (d) Monthly and annual total number of observations.
- NOTE: See note under Table 2.

Table 5 -Air-sea temperature differences

- (a) Monthly means;
 - (b) Mean for the year, computed from monthly means;
 - (c) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
 - (d) Monthly and annual total number of observations.
- NOTE: See note under Table 2.

Table 6 -Visibility

- (a) Number of observations for each month for each code figure 90-99 (WMO code table 4377);
- (b) Total number of observations for the year for each code 90-99;
- (c) Monthly and annual total of observations.

Table 7 -Weather

- (a) Monthly number of occasions with rain or drizzle at the time of observation (ww = 50-67, 80-82 (WMO code table 4677));
- (b) Monthly number of occasions with snow or snow and rain at the time of observation (ww = 68-79, 83-86);
- (c) Monthly number of occasions with hail at the time of observation (ww = 87-90);
- (d) Monthly number of occasions with thunderstorms at the time of observation (ww = 17, 91-99);
- (e) Monthly number of observations with:

- (i) Gales (Beaufort force ≥ 8);
- (ii) Storms (Beaufort force ≥ 10);
- (iii) Hurricane force winds (Beaufort force = 12) at the time of observation;
- (f) Monthly number of occasions of precipitation at the time of observation (ww = 50-97, 99);
- (g) Annual number of occasions for each item (a) to (f);
- (h) Monthly and annual total number of observations.

NOTES: (1) A column "VIS < 1 km" (visibility less than 1 km) should be added between the "precipitation" column and the "total number of observations" column.

(2) Responsible Members may include additional non-standard tables for those phenomena which are of importance for particular climatic regions as an appendix to the summary.

Table 8 -Wind direction and force

- (a) Monthly number of observations for each month for each Beaufort number 0, 1, 2, etc., and for directions by sectors of 30° , true north bisecting the first sector;
- (b) Monthly total of observations for each sector irrespective of wind force;
- (c) Monthly number of observations for each Beaufort number irrespective of direction;
- (d) Mean monthly wind force according to the Beaufort scale, derived from all wind observations;
- (e) Mean wind force for the year, computed from monthly means;
- (f) Monthly and annual total number of observations.

NOTE: The column "mean force in Beaufort" should be left blank until an appropriate method of representing such a mean is determined.

Table 9 - Sea-level pressure

- (a) Monthly means for all hours of observation;
- (b) Mean for the year, computed from monthly means;
- (c) Frequency table in:
 - (i) 2-hPa steps between 0° and 30° latitude, based on the intervals 0.0 to 1.9 hPa, e.g. 990.0 to 991.9 hPa;
 - (ii) 4-hPa steps N of 30° N and S of 30° S, based on the intervals 0.0 to 3.9 hPa, e.g. 996.0 to 999.9 hPa;
- (d) Monthly and annual total number of observations.

NOTES: (1) At the bottom of the table, lines should be added showing pressure averages by hour for the 0000, 0600, 1200 and 1800 UTC observations; an account of the number of observations should be included under each list of pressure averages.

(2) See note under Table 2.

Table 10 - Cloud

- (a) Monthly mean of total cloud amount;
- (b) Monthly mean amount for low cloud only (defined as cloud for which h is any code figure from 0 to 8 inclusive (WMO code table 1600));
- (c) Monthly and annual number of observations in the following ranges of total cloud amount:
 - (i) 2 oktas or less;
 - (ii) 3 to 5 oktas inclusive;
 - (iii) 6 to 7 oktas;
 - (iv) 8 oktas;
- (d) Mean for the year for items (a) and (b), computed from monthly means;
- (e) Monthly and annual total of observations.

NOTE: The table should include the following note: 'Mean low cloud' means amount for low cloud only (defined as cloud for which h is any code figure from 0 to 8 inclusive (WMO code table 1600)).

Table 11 - Waves

Tables as for fixed stations.

APPENDIX I.14

PARAMETERS TO BE INCLUDED IN MARINE CLIMATOLOGICAL SUMMARIES FOR SELECTED REPRESENTATIVE AREAS IN POLAR REGIONS

Table 1 -Mean position of all observations

- (a) Monthly mean position of all observations;
- (b) Mean position for the year as calculated from the monthly mean positions.

Table 2 -Air temperature

- (a) Monthly means;
- (b) Frequency table in 3°C steps based on the intervals 0.0 to 2.9°C (positive values), -0.1 to -3.0°C (negative values), or where and when necessary in 1°C steps based on the intervals 0.0 or 0.9°C (positive values), -0.1 to -1.0°C (negative values);
- (c) Extreme values should be included when 3°C steps are used under (b);
- (d) Standard deviations, if the number of observations is sufficiently large;
- (e) Monthly number of observations.

Table 3 -Dew-point temperature

This table is not included.

Table 4 -Sea-surface temperature

- (a) Monthly means;
- (b) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
- (c) Monthly number of observations.

Table 5 -Air-sea temperature difference

- (a) Monthly means;
- (b) Frequency table in 1°C steps based on the intervals 0.0 to 0.9°C (positive values), -0.1 to -1.0°C (negative values), e.g. 9.0 to 9.9°C, -1.1 to -2.0°C;
- (c) Monthly number of observations.

Table 6 -Visibility

- (a) Number of observations for each month for each code figure 90-99 (WMO code table 4377);
- (b) Monthly number of observations.

Table 7 - Weather

- (a) Monthly number of occasions with rain or drizzle at the time of observation (ww =50-67, 80-82 (WMO code table 4677));
- (b) Monthly number of occasions with snow or snow and rain at the time of observation (ww = 68-79, 83-86);
- (c) Monthly number of occasions with hail at the time of observation (ww = 87-90);
- (d) Monthly number of occasions with current or recent thunderstorms with or without precipitation at the time of observation (ww = 17, 91-99);
- (e) Monthly number of observations with:
 - (i) Gales (Beaufort force ≥ 8);
 - (ii) Storms (Beaufort force ≥ 10);
 - (iii) Hurricane force winds (Beaufort force = 12);
- (f) Monthly number of occasions of precipitation at the time of observation (ww = 50-97, 99);
- (g) Monthly number of occasions of visibility less than 1 km;
- (h) Monthly number of observations.

Table 8 - Wind direction and force

- (a) Monthly number of observations for each month for each Beaufort number 0, 1, 2, etc., and for direction by sectors of 30°, true north bisecting the first sector;

- (b) Monthly total of observations for each sector irrespective of wind force;
- (c) Monthly total of observations for each Beaufort number irrespective of direction;
- (d) Monthly number of observations.

Table 9 - Sea-level pressure

- (a) Monthly means and extremes for all hours of observation;
- (b) Frequency table in 4 hPa steps, based on the intervals 0.0 to 3.9 hPa, e.g. 996.0 to 999.9 hPa;
- (c) Standard deviations, if the number of observations is sufficiently large;
- (d) Monthly number of observations.

Table 10 - Cloud

- (a) Monthly mean of total cloud amount;
- (b) Monthly mean amount for low cloud only (defined as cloud for which h is any code figure from 0 to 8 inclusive (WMO code table 1600));
- (c) Monthly number of observations in the following ranges of total cloud amount:
 - (i) 2 oktas or less;
 - (ii) 3 to 5 oktas inclusive;
 - (iii) 6 to 7 oktas;
 - (iv) 8 oktas;
- (d) Monthly number of observations.

Table 11 - Waves

List of original observations or, where number of observations is sufficient, seasonal tables as for fixed ship stations.

APPENDIX I.15

LAYOUT FOR THE INTERNATIONAL MARITIME METEOROLOGICAL TAPE (IMMT) FORMAT IMMT-5 (Version 5)

Notes:

- (a) The representation for missing data in any field is all blank(s).
- (b) Many of the “Codes” in the IMMT format match “symbolic letters” as defined in the *Manual on Codes* (WMO–No.306) for the traditional alphanumeric (e.g. FM 13) SHIP code. However, the elements added for the VOSClm project (as introduced for IMMT-2), for example, did not appear in WMO–No.306, thus an effort was made to select unique new Codes to avoid conflicts in meaning between symbolic letter groups in WMO–No.306 versus Codes defined only in IMMT.

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
1	1	i _T	Format/temperature indicator	3 – temperatures in tenths of °C 4 – temperatures in halves of °C 5 – temperatures in whole °C [Note: codes 1-2 were previously used to refer to the obsolete IMMPC format; current codes all refer to the IMMT format]
2	2-5	AAAA	Year UTC	Four digits
3	6-7	MM	Month UTC	01 – 12 January to December
4	8-9	YY	Day UTC	01 – 31
5	10-11	GG	Time of observation	Nearest whole hour UTC, WMO specifications
6	12	Qc	Quadrant of the globe	WMO code table 3333
7	13-15	L _a L _a L _a	Latitude	Tenths of degrees, WMO specifications
8	16-19	L _o L _o L _o L _o	Longitude	Tenths of degrees
9	20		Cloud height (h) and visibility (VV) measuring indicator	0 – h and VV estimated 1 – h measured, VV estimated 2 – h and VV measured 3 – h estimated, VV measured
10	21	h	Height of clouds	WMO code table 1600
11	22-23	VV	Visibility	WMO code table 4377
12	24	N	Cloud amount	Oktas, WMO code table 2700; show 9 where applicable
13	25-26	dd	True wind direction	Tens of degrees, WMO code table 0877; show 00 or 99 where applicable
14	27	i _w	Indicator for wind speed	WMO code table 1855
15	28-29	ff	Wind speed	Units of knots or meters per second, hundreds omitted; values in excess of 99 knots are to be indicated in units of meters per second and i _w encoded accordingly; the method of estimation or measurement and the units used (knots or meters per second) are indicated in element 14. Wind is at observation height or anemometer height (i.e. it is not reduced to 10m).

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
16	30	s _n	Sign of temperature	WMO code table 3845
17	31-33	TTT	Air temperature	Tenths of degrees Celsius
18	34	s _t	Sign of dew-point temperature	0 – positive or zero measured dew-point temperature 1 – negative measured dew-point temperature 2 – iced measured dew-point temperature 5 – positive or zero computed dew-point temperature 6 – negative computed dew-point temperature 7 – iced computed dew-point temperature
19	35-37	T _d T _d T _d	Dew-point temperature	Tenths of degrees Celsius
20	38-41	PPPP	Air pressure	Tenths of hectopascals
21	42-43	ww	Present weather	WMO code table 4677 or 4680
22	44	W ₁	Past weather	WMO code table 4561 or 4531
23	45	W ₂	Past weather	WMO code table 4561 or 4531
24	46	N _h	Amount of lowest clouds	As reported for C _L or, if no C _L cloud is present, for C _M , in oktas; WMO code table 2700
25	47	C _L	Genus of CL clouds	WMO code table 0513
26	48	C _M	Genus of CM clouds	WMO code table 0515
27	49	C _H	Genus of CH clouds	WMO code table 0509
28	50	s _n	Sign of sea-surface temperature	WMO code table 3845
29	51-53	T _w T _w T _w	Sea surface temperature	Tenth of degrees Celsius
30	54		Indicator for sea-surface temperature measurement	0 – Bucket thermometer 1 – Condenser inlet 2 – Trailing thermistor 3 – Hull contact sensor 4 – “Through hull” sensor 5 – Radiation thermometer 6 – Bait tanks thermometer 7 – Others
31	55		Indicator for wave measurement	Shipborne wave recorder
				0 – Wind sea and swell estimated 1 – Wind sea and swell measured 2 – Mixed wave measured, swell estimated 3 – Other combinations measured and estimated
31	55		Indicator for wave measurement	Buoy
				4 – Wind sea and swell measured 5 – Mixed wave measured, swell estimated 6 – Other combinations measured and estimated

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				<div>Other measurement system</div> <div> 7 – Wind sea and swell measured 8 – Mixed wave measured, swell estimated 9 – Other combinations measured and estimated </div>
32	56-57	P _W P _W	Period of wind waves or of measured waves	Whole seconds; show 99 where applicable in accordance with Note (3) under specification of P _W P _W in WMO–No.306.
33	58-59	H _W H _W	Height of wind waves or of measured waves	Half-meter values. Examples: Calm or less than ¼m to be encoded 00; 3½m to be encoded 07; 7m to be encoded 14; 11½m to be encoded 23.
34	60-61	d _{W1} d _{W1}	Direction of predominant swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks = no observation of waves attempted.
35	62-63	P _{W1} P _{W1}	Period of predominant swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
36	64-65	H _{W1} H _{W1}	Height of predominant swell waves	Half-meter values (see under element 33)
37	66	I _s	Ice accretion on ships	WMO code table 1751
38	67-68	E _s E _s	Thickness of ice accretion	In centimeters
39	69	R _s	Rate of ice accretion	WMO code table 3551
40	70		Source of observation	0 – Unknown 1 – Logbook (paper) 2 – National Telecommunication channels 3 – National Publications 4 – Logbook (electronic) 5 – Global Telecommunication channels (GTS) 6 – International Publications [Note: Formerly (usage now discontinued): codes 1-3 also referred to “National data exchange,” and codes 4-6 also referred to “International data exchange”; distinction added between paper and electronic logbook]
41	71		Observation platform	0 – Unknown 1 – Selected ship 2 – Supplementary ship 3 – Auxiliary ship 4 – Registered VOSclim ship 5 – Fixed sea station (e.g., rig or platform) 6 – Coastal station [Note: 7 – Reserved] [Note: 8 – Reserved] 9 – Others/data buoy [Note: Formerly (usage now discontinued): code 4 referred to “Automated station/data buoy,” and codes 7-8 referred to “Aircraft” and “Satellite,” respectively]
42	72-78		Ship's call sign	Ship's call sign stored left-justified (with right-blank fill) as follows: 7-character call sign: columns 72–78

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				6-character call sign: columns 72–77 5-character call sign: columns 72–76 4-character call sign: columns 72–75 3-character call sign: columns 72–74
43	79-80		Country which has recruited the ship	According to the 2-character alphabetical codes assigned by the International Organization for Standardization (ISO)
44	81		National use	
45	82		Quality control indicator	0 – no QC has been performed 1 – manual QC only 2 – automated QC only (such as using only MQC) 3 – automated QC only (with time sequence checks) 4 – manual and automated QC (superficial) 5 – manual and automated QC (superficial; with time-sequence checks) 6 – manual and automated QC (intensive; with time-sequence checks) 7 – [reserved] 8 – [reserved] 9 – national system of QC (information to be furnished to WMO)
46	83	i _x	Weather data indicator	1 – Manual
				4 – Automatic
				7 – Automatic
				If present and past weather data included Code tables 4677 and 4561 used If present and past weather data included Code tables 4680 and 4531 used
47	84	i _R	Indicator for inclusion or omission of precipitation data	WMO code table 1819
48	85-87	RRR	Amount of precipitation which has fallen during the period preceding the time of observation, as indicated by t _R	WMO code table 3590
49	88	t _R	Duration of period of reference for amount of precipitation, ending at the time of the report	WMO code table 4019
50	89	s _w	Sign of wet-bulb temperature	0 – positive or zero measured wet-bulb temperature 1 – negative measured wet-bulb temperature 2 – iced measured wet-bulb temperature 5 – positive or zero computed wet-bulb temperature 6 – negative computed wet-bulb temperature 7 – iced computed wet-bulb temperature

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
51	90-92	T _b T _b T _b	Wet-bulb temperature	In tenths of degree Celsius, sign given by element 50
52	93	a	Characteristic of pressure tendency during the three hours preceding the time of observation	WMO code table 0200
53	94-96	ppp	Amount of pressure tendency at station level during the three hours preceding the time of observation	In tenths of hectopascal
54	97	D _s	True direction of resultant displacement of the ship during the three hours preceding the time of observation	WMO code table 0700
55	98	v _s	Ship's average speed made good during the three hours preceding the time of observation	WMO code table 4451
56	99-100	d _{w2} d _{w2}	Direction of secondary swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks – no observation of waves attempted.
57	101-102	P _{w2} P _{w2}	Period of secondary swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
58	103-104	H _{w2} H _{w2}	Height of secondary swell waves	Half-meter values (see under element 33)
59	105	c _i	Concentration or arrangement of sea ice	WMO code table 0639
60	106	S _i	Stage of development	WMO code table 3739
61	107	b _i	Ice of land origin	WMO code table 0439
62	108	D _i	True bearing of principal ice edge	WMO code table 0739
63	109	z _i	Present ice situation and trend of conditions over the preceding three hours	WMO code table 5239
64	110		FM code version	0 – previous to FM 24-V 1 – FM 24-V 2 – FM 24-VI Ext. 3 – FM 13-VII 4 – FM 13-VIII 5 – FM 13-VIII Ext. 6 – FM 13-IX 7 – FM 13-IX Ext. 8 – FM 13-X

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				9 – FM 13-XI A – FM 13-XII Ext. B – FM 13-XIII C – FM 13-XIV Ext. [Note: etc. for future configurations]
65	111		IMMT version	0 – IMMT version just prior to version number being included 1 – IMMT-1 (in effect from 2 Nov. 1994) 2 – IMMT-2 (in effect from Jan. 2003) 3 – IMMT-3 (in effect from Jan. 2007) 4 – IMMT-4 (in effect from Jan. 2011) 5 – IMMT-5 (in effect from June 2012) [Note: etc. for future configurations]
66	112	Q ₁	Quality control indicator for (h)	0 – no QC has been performed on this element 1 – QC performed; element appears correct 2 – QC performed; element appears inconsistent with other elements 3 – QC performed; element appears doubtful 4 – QC performed; element appears erroneous 5 – QC performed; element changed (possibly to missing) as a result 6 – QC flag amended: element flagged by CM as correct (1), but according to MQCS still appears suspect (2-4) or missing (9) 7 – QC flag amended: element flagged by CM as changed (5), but according to MQCS still appears suspect (2-4) 8 – [reserved] 9 – element is missing
67	113	Q ₂	QC indicator for (VV)	- idem -
68	114	Q ₃	QC indicator for (N and clouds: elements 12, 24–27)	- idem -
69	115	Q ₄	QC indicator for (dd)	- idem -
70	116	Q ₅	QC indicator for (ff)	- idem -
71	117	Q ₆	QC indicator for (s _n and TTT)	- idem -
72	118	Q ₇	QC indicator for (s _t and T _d T _d T _d)	- idem -
73	119	Q ₈	QC indicator for (PPPP)	- idem -
74	120	Q ₉	QC indicator for (weather: ww, W ₁ , W ₂ ; elements 21–23)	- idem -
75	121	Q ₁₀	QC indicator for (s _n and T _w T _w T _w)	- idem -
76	122	Q ₁₁	QC indicator for (P _w P _w)	- idem -
77	123	Q ₁₂	QC indicator for (H _w H _w)	- idem -
78	124	Q ₁₃	QC indicator for	- idem -

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
			(swell: elements 34–36, 56–58)	
79	125	Q ₁₄	QC indicator for (i _R RRRt _R)	- idem -
80	126	Q ₁₅	QC indicator for (a)	- idem -
81	127	Q ₁₆	QC indicator for (ppp)	- idem -
82	128	Q ₁₇	QC indicator for (D _s)	- idem -
83	129	Q ₁₈	QC indicator for (v _s)	- idem -
84	130	Q ₁₉	QC indicator for (s _w and T _b T _b T _b)	- idem -
85	131	Q ₂₀	QC indicator for ships' position	- idem -
86	132	Q ₂₁	Version identification for Minimum Quality Control Standard (MQCS)	1 – MQCS-1 (Original version, Feb. 1989): CMM-X 2 – MQCS-2 (Version 2, March 1997) CMM-XII 3 – MQCS-3 (Version 3, April 2000) SGMC-VIII 4 – MQCS-4 (Version 4, June 2001): JCOMM-I 5 – MQCS-5 (Version 5, July 2004): ETMC-I 6 – MQCS-6 (Version 6, November 2009)) JCOMM-III 7 – MQCS-7 (Version 7, in effect from June 2012) JCOMM-IV [Note: etc. for future configurations]
87	133-135	HDG	Additional Requirements for VOSClm: Ship's heading; the direction to which the bow is pointing, referenced to true North	(001-360); e.g. 360 = North 090 = East
88	136-138	COG	Ship's ground course; the direction the vessel actually moves over the fixed earth and referenced to True North	(000-360); e.g. 360 = North 000 = No Movement 090 = East
89	139-140	SOG	Ship's ground speed; the speed the vessel actually moves over the fixed earth	(00-99); Round to nearest whole knot
90	141-142	SLL	Maximum height in meters of deck cargo above Summer maximum load line (reference level)	(00-99); Round to nearest whole meter
91	143	s _L	Sign of departure of reference level	0 = positive or zero, 1 = negative

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
92	144-145	hh	Departure of reference level (Summer maximum load line) from actual sea level	Difference to the nearest whole meter (00-99) between the Summer maximum load line and the sea level (water line); positive when the Summer maximum load line is above the level of the sea and negative if below the water line
93	146-148	RWD	Relative wind direction in degrees off the bow	Relative wind direction; e.g. 000 = no apparent relative wind speed (calm conditions on deck). Reported direction for relative wind = 001-360 degrees in a clockwise direction off the bow of the ship. When directly on the bow, RWD = 360.
94	149-151	RWS	Relative wind speed indicated by i_w (knots or $m\ s^{-1}$)	Reported in either whole knots or whole meters per second (e.g. 010 knots or 005 $m\ s^{-1}$). Units established by i_w (element 14) [Note: RWS is a 3-character field to store values of RWS larger than ff (if i_w indicates knots), e.g. ff=98 knots, RWS=101 knots; see also element 15.]
95	152	Q ₂₂	QC indicator for (HDG)	[Note: coding as for element 66]
96	153	Q ₂₃	QC indicator for (COG)	– idem –
97	154	Q ₂₄	QC indicator for (SOG)	– idem –
98	155	Q ₂₅	QC indicator for (SLL)	– idem –
	156		blank	[Note: Formerly (usage now discontinued): QC indicator for (s_L); now Q ₂₇ serves as the indicator for both s_L and hh]
99	157	Q ₂₇	QC indicator for (s_L and hh)	– idem –
100	158	Q ₂₈	QC indicator for (RWD)	– idem –
101	159	Q ₂₉	QC indicator for (RWS)	– idem –
102	160-163	RH	Relative humidity	Tenths of Percentage
103	164	RHi	Relative humidity indicator	0 – Relative humidity in tenths of Percentage, measured and originally reported 1 – Relative humidity in whole Percentage, measured and originally reported [Note: 2 – Reserved] 3 – Relative humidity in tenths of Percentage, computed 4 – Relative humidity in whole Percentage, computed
104	165	AWSi	AWS indicator	0 – No Automated Weather Station (AWS) 1 – AWS 2 – AWS plus Manual Observation
105	166-172	IMOno	IMO number	Seven digits (or left justified with right-blank fill)

APPENDIX I.16

LAYOUT FOR MARITIME METEOROLOGICAL TAPE FOR POSSIBLE USE IN
NATIONAL AND BILATERAL DATA EXCHANGE

Element No.	Element	Character No.
1	Format and temperature indicator (i_T) (Same as Col. 1 of IMMPC)	1
2	AA	2-3
3	MM	4-5
4	YY	6-7
5	GG	8-9
6	i_w	10
7	Q	11
8	$L_a L_a L_a$	12-14
9	$L_o L_o L_o$	15-17
10	Indicator for h and VV	18
11	h	19
	Q_1	20
12	VV	21-22
	Q_2	23
13	N	24
	Q_3	
14	dd	25-26
	Q_4	27
15	ff	28-29
	Q_5	30
16	s_n	31
17	TTT	32-34
	Q_6	35
18	Sign of reported wet-bulb or dew-point temperature	36
19	Wet-bulb/dew-point temperature	37-39
	Q_7	40
20	PPPP	41-44
	Q_8	45
21	ww	46-47
22	W_1	48
23	W_2	49
	Q_9	50
24	N_h	51
25	C_L	52
Element No.	Element	Character No.
26	C_M	53
27	C_H	54

	Q_3	55
28	s_n	56
29	$T_w T_w T_w$	57-59
	Q_{10}	60
30	Indicator for SST measurement	61
31	Indicator for wave measurement	62
32	$P_w P_w$	63-64
	Q_{11}	65
33	$H_w H_w$	66-67
	Q_{12}	68
34	$d_{w1} d_{w1}$	69-70
35	$P_{w1} P_{w1}$	71-72
36	$H_{w1} H_{w1}$	73-74
	Q_{13}	
37	I_s	75
38	$E_s E_s$	76-77
39	R_s	78
40	Source of observation	79
41	Observation platform	80
42	Ship identifier	81-87
43	Country which has recruited ship	88-89
44	Quality control indicator	90
45	i_x	91
46	National use	92
47	i_R	93
48	RRR	94-96
	Q_{14}	97
49	t_R	98
50	Sign of computed wet-bulb or dew-point temperature	99
51	Computed wet-bulb or dew-point temperature	100-102
52	a	103
	Q_{15}	104
53	ppp	105-107
	Q_{16}	108
54	D_s	109
	Q_{17}	110
55	v_s	111
	Q_{18}	112
Element No.	Element	Character No.
56	$d_{w2} d_{w2}$	113-114
57	$P_{w2} P_{w2}$	115-116
58	$H_{w2} H_{w2}$	117-118
	Q_{13}	119

59	c_i	120
60	S_i	121
61	b_i	122
62	D_i	123
63	z_i	124

Quality control indicators (Q_1 to Q_{18}) for elements indicated in brackets

Q_1 (h)	20
Q_2 (VV)	23
Q_3 (clouds: elements 13, 24-27)	55
Q_4 (dd)	27
Q_5 (ff)	30
Q_6 (TTT)	35
Q_7 (wet bulb/dew point)	40
Q_8 (PPPP)	45
Q_9 (weather: elements 21, 22, 23)	50
Q_{10} ($T_w T_w T_w$)	60
Q_{11} ($P_w P_w$)	65
Q_{12} ($H_w H_w$)	68
Q_{13} (swell: elements 34-36, 56-58)	119
Q_{14} (i_R RRR t_R)	97
Q_{15} (a)	104
Q_{16} (ppp)	108
Q_{17} (D_s)	110
Q_{18} (v_s)	112

Specifications for quality control indicators Q_1 to Q_{18}

0	No quality control (QC) has been performed on this element
1	QC has been performed; element appears to be correct
2	QC has been performed; element appears to be inconsistent with other element
3	QC has been performed; element appears to be doubtful
4	QC has been performed; element appears to be erroneous
5	The value has been changed as a result of QC
6 - 8	Reserve
9	The value of the element is missing

APPENDIX I.17

MINIMUM QUALITY CONTROL STANDARD (MQCS)
MQCS-7 (Version 7)

Notes:

- (a) See the specifications for setting quality control Indicators Q_1 to Q_{29} at the end of this Annex
 (b) Δ = space (ASCII 32)

<u>Element</u>	<u>Error</u>	<u>Action</u>
1	$i_T \neq 3 - 5, \Delta$	Correct manually otherwise 3
2	AAAA \neq valid year	Correct manually otherwise reject
3	MM \neq 01 - 12	Correct manually otherwise reject
4	YY \neq valid day of month	Correct manually otherwise reject
5	GG \neq 00 - 23	Correct manually otherwise reject
6	$Q_C \neq 1, 3, 5, 7$ $Q_C = \Delta$	Correct manually and $Q_{20} = 5$, otherwise $Q_{20} = 4$ $Q_{20} = 2$
7	$L_a L_a L_a \neq 000-900$ $L_a L_a L_a = \Delta\Delta\Delta$	Correct manually and $Q_{20} = 5$, otherwise $Q_{20} = 4$ $Q_{20} = 2$
8	$L_o L_o L_o L_o \neq 0000-1800$ $L_o L_o L_o L_o = \Delta\Delta\Delta\Delta$ $L_a L_a L_a = L_o L_o L_o L_o = \Delta\Delta\Delta(\Delta)$	Correct manually and $Q_{20} = 5$, otherwise $Q_{20} = 4$ $Q_{20} = 2$ Correct manually otherwise reject
<u>Time sequence checks</u>		
	Change in latitude $> 0.7^\circ/\text{hr}$	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 0.7^\circ/\text{hr}$ when lat. 00-39.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 1.0^\circ/\text{hr}$ when lat. 40-49.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 1.4^\circ/\text{hr}$ when lat. 50-59.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 2.0^\circ/\text{hr}$ when lat. 60-69.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 2.7^\circ/\text{hr}$ when lat. 70-79.9	Correct manually otherwise $Q_{20} = 3$
9	Indicator $\neq 0-3, \Delta$	Correct manually, otherwise Δ
10	$h \neq 0-9$ $h = \Delta$	Correct manually and $Q_1 = 5$, otherwise $Q_1 = 4$ $Q_1 = 9$
11	$VV \neq 90-99$ $VV = \Delta\Delta$	Correct manually and $Q_2 = 5$, otherwise $Q_2 = 4$ $Q_2 = 9$
12	$N \neq 0-9, \Delta$ $N < N_h$	Correct manually and $Q_3 = 5$, otherwise $Q_3 = 4$ Correct manually and $Q_3 = 5$, otherwise $Q_3 = 2$
13	$dd \neq 00-36, 99$ $dd = \Delta\Delta$ dd versus ff $dd = 00, ff \neq 00$ $dd \neq 00, ff = 00$	Correct manually and $Q_4 = 5$, otherwise $Q_4 = 4$ $Q_4 = 9$ Correct manually and Q_4 or $Q_5 = 5$ otherwise $Q_4 = Q_5 = 2$ Correct manually and Q_4 or $Q_5 = 5$ otherwise $Q_4 = Q_5 = 2$
14	$i_w \neq 0, 1, 3, 4$	Correct manually, otherwise $Q_5 = Q_{29} = 4$
15	$ff > 80$ knots $ff = \Delta\Delta$	Correct manually and $Q_5 = 5$, otherwise $Q_5 = 3$ $Q_5 = 9$
16	$s_n \neq 0, 1$	Correct manually, otherwise $Q_6 = 4$
17	$TTT = \Delta\Delta\Delta$ If $-25 > TTT > 40$ then when Lat. < 45.0 $TTT < -25$ $TTT > 40$ when Lat. ≥ 45.0 $TTT < -25$ $TTT > 40$	$Q_6 = 9$ $Q_6 = 4$ $Q_6 = 3$ $Q_6 = 3$ $Q_6 = 4$
<u>TTT versus humidity parameters</u>		

<u>Element</u>	<u>Error</u>	<u>Action</u>
	TTT < WB (wet bulb) TTT < DP (dew point)	Correct manually and $Q_6 = 5$, otherwise $Q_6=Q_{19}= 2$ Correct manually and $Q_6 = Q_7 = 5$, otherwise $Q_6 = Q_7 = 2$
18	$s_t \neq 0, 1, 2, 5, 6, 7$	Correct manually, otherwise $Q_7 = 4$
19	DP > WB DP > TTT WB = DP = $\Delta\Delta\Delta$	Correct manually and $Q_7 = 5$, otherwise $Q_7=Q_{19} = 2$ Correct manually and $Q_7 = 5$, otherwise $Q_7 = Q_6 = 2$ $Q_7 = Q_{19} = 9$
20	930 > PPPP > 1050 hPa 870 > PPPP > 1070 hPa PPPP = $\Delta\Delta\Delta\Delta$	Correct manually and $Q_8 = 5$, otherwise $Q_8 = 3$ Correct manually and $Q_8 = 5$, otherwise $Q_8 = 4$ $Q_8 = 9$
21	ww = 22-24, 26, 36-39, 48, 49, 56, 57, 66-79, 83-88 93-94 and latitude <20° if $i_x = 7$: $w_a w_a = 24 - 25, 35, 47-48, 54-56, 64-68,$ 70-78, 85-87 and latitude <20°	Correct manually and $Q_9 = 5$, otherwise $Q_9 = 4$ Correct manually and $Q_9 = 5$, otherwise $Q_9 = 3$ Correct manually and $Q_9 = 5$, otherwise $Q_9 = 4$
22, 23	W_1 or $W_2 = 7$ and latitude <20° $W_1 < W_2$ $W_1 = W_2 = ww = \Delta\Delta\Delta\Delta$	Correct manually and $Q_9 = 5$, otherwise $Q_9 = 4$ Correct manually and $Q_9 = 5$, otherwise $Q_9 = 2$ $Q_9 = 9$
24-27	$N = 0$, and $N_h C_L C_M C_H \neq 0000$ $N = \Delta$, and $N_h C_L C_M C_H \neq \Delta\Delta\Delta\Delta$ $N = 9$, and not ($N_h = 9$ and $C_L C_M C_H$ $\neq \Delta\Delta\Delta$ $N = \Delta$, and $N_h C_L C_M C_H = \Delta\Delta\Delta\Delta$	Correct manually and $Q_3 = 5$, otherwise $Q_3 = 2$ Correct manually and $Q_3 = 5$, otherwise $Q_3 = 2$ Correct manually and $Q_3 = 5$, otherwise $Q_3 = 2$ $Q_3 = 9$
28	$s_n \neq 0, 1$	Correct manually otherwise $Q_{10} = 4$
29	$T_w T_w T_w = \Delta\Delta\Delta$ if $-2.0 > T_w T_w T_w > 37.0$ then when Lat. < 45.0 $T_w T_w T_w < -2.0$ $T_w T_w T_w > 37.0$ when Lat. ≥ 45.0 $T_w T_w T_w < -2.0$ $T_w T_w T_w > 37.0$	$Q_{10} = 9$ Control manually and $Q_{10} = 5$, otherwise $Q_{10} = 4$ Control manually and $Q_{10} = 5$, otherwise $Q_{10} = 3$ Control manually and $Q_{10} = 5$, otherwise $Q_{10} = 3$ Control manually and $Q_{10} = 5$, otherwise $Q_{10} = 4$
30	Indicator $\neq 0-7, \Delta$	Correct manually, otherwise Δ
31	Indicator $\neq 0-9, \Delta$	Correct manually, otherwise Δ
32	$20 < P_w P_w < 30$ $P_w P_w \geq 30$ and $\neq 99$ $P_w P_w = \Delta\Delta$	$Q_{11} = 3$ $Q_{11} = 4$ $Q_{11} = 9$
33	$35 < H_w H_w < 50$ $H_w H_w \geq 50$ $H_w H_w = \Delta\Delta$	$Q_{12} = 3$ $Q_{12} = 4$ $Q_{12} = 9$
34	$d_{w1} d_{w1} \neq 00-36, 99$ $swell_1 = swell_2 = \Delta$	Correct manually and $Q_{13} = 5$, otherwise $Q_{13} = 4$ $Q_{13} = 9$
35	$25 < P_{w1} P_{w1} < 30$ $P_{w1} P_{w1} \geq 30$ and $\neq 99$	$Q_{13} = 3$ $Q_{13} = 4$
36	$35 < H_{w1} H_{w1} < 50$ $H_{w1} H_{w1} \geq 50$	$Q_{13} = 3$ $Q_{13} = 4$
37	$I_s \neq 1-5, \Delta$	Correct manually, otherwise Δ
38	$E_s E_s \neq 00-99, \Delta\Delta$	Correct manually, otherwise $\Delta\Delta$
39	$R_s \neq 0-4, \Delta$	Correct manually, otherwise Δ
40	Source $\neq 0-6$	Correct manually, otherwise Δ
41	Platform $\neq 0-9$	Correct manually, otherwise Δ
42	No call sign	Insert manually, mandatory entry
43	No country code	Insert manually
44	No Quality Control	
45	$Q \neq 0-6, 9$	Correct manually, otherwise Δ
46	$i_x \neq 1-7$	Correct manually, otherwise Δ
47	$i_R = 0-2$ and $RRR = 000, \Delta\Delta\Delta$ $i_R = 3$ and $RRR \neq \Delta\Delta\Delta$ $i_R = 4$ and $RRR \neq \Delta\Delta\Delta$ $i_R \neq 0-4$	Correct manually, otherwise $Q_{14} = 4$ Correct manually, otherwise $Q_{14} = 2$ Correct manually, otherwise $Q_{14} = 2$ Correct manually, otherwise $Q_{14} = 4$
48	$RRR \neq 001-999$ and $i_R = 1, 2$	Correct manually and $Q_{14} = 5$, otherwise $Q_{14} = 2$
49	$t_R \neq 0-9, \Delta$	Correct manually and $Q_{14} = 5$, otherwise $Q_{14} = 4$
50	$s_w \neq 0, 1, 2, 5, 6, 7$	Correct manually, otherwise $Q_{19} = 4$

<u>Element</u>	<u>Error</u>	<u>Action</u>
51	WB < DP WB = $\Delta\Delta\Delta$ WB > TTT	Correct manually and $Q_{19} = 5$, otherwise $Q_{19}=Q_7=2$ $Q_{19} = 9$ Correct manually and $Q_{19}= 5$, otherwise $Q_{19}=Q_6=2$
52	$a \neq 0-8$ $a = 4$ and $ppp \neq 000$ $a = 1,2,3,6,7,8$ and $ppp=000$	Correct manually and $Q_{15} = 5$, otherwise $Q_{15} = 4$ Correct manually and Q_{15} or $Q_{16} = 5$, otherwise $Q_{15}=Q_{16}=2$ Correct manually and Q_{15} or $Q_{16} = 5$, otherwise $Q_{15}=Q_{16} = 2$ $Q_{15} = 9$
53	$a = \Delta$ $250 \geq ppp > 150$ $ppp > 250$ $ppp = \Delta\Delta\Delta$	Correct manually and $Q_{16} = 5$, otherwise $Q_{16} = 3$ Correct manually and $Q_{16} = 5$ otherwise $Q_{16} = 4$ $Q_{16} = 9$
54	$D_s \neq 0-9$ $D_s = \Delta$	Correct manually and $Q_{17} = 5$, otherwise $Q_{17} = 4$ $Q_{17} = 9$
55	$V_s \neq 0-9$ $V_s = \Delta$	Correct manually and $Q_{18} = 5$, otherwise $Q_{18} = 4$ $Q_{18} = 9$
56	$d_{w2}d_{w2} \neq 00-36, 99, \Delta\Delta$	Correct manually and $Q_{13} = 5$, otherwise $Q_{13} = 4$
57	$25 < P_{w2}P_{w2} < 30$ $P_{w2}P_{w2} \geq 30$ and $\neq 99$	$Q_{13} = 3$ $Q_{13} = 4$
58	$35 < H_{w2}H_{w2} < 50$ $H_{w2}H_{w2} \geq 50$	$Q_{13} = 3$ $Q_{13} = 4$
59	$c_i \neq 0-9, \Delta$	Correct manually, otherwise Δ
60	$S_i \neq 0-9, \Delta$	Correct manually, otherwise Δ
61	$b_i \neq 0-9, \Delta$	Correct manually, otherwise Δ
62	$D_i \neq 0-9, \Delta$	Correct manually, otherwise Δ
63	$z_i \neq 0-9, \Delta$	Correct manually, otherwise Δ
64	version $\neq 0-9, A-C, \Delta$	Correct manually, otherwise Δ
65	version $\neq 0-4, \Delta$	Correct manually, otherwise Δ
86	Minimum Quality Control Standard (MQCS) version identification	1= MQCS-1 (Original version, Feb. 1989) CMM-X 2= MQCS-2 (Version 2, March 1997) CMM-XII 3= MQCS-3 (Version 3, April 2000) SGM-C-VIII 4= MQCS-4 (Version 4, June 2001) JCOMM-I 5= MQCS-5 (Version 5, July 2004) ETMC-I 6 = MQCS-6 (Version 6, November 2009) JCOMM-III) 7 = MQCS-7 (Version 7, in effect from June 2012) JCOMM-IV
87	HDG $\neq 001-360$ HDG = $\Delta\Delta\Delta$	Correct manually and $Q_{22} = 5$, otherwise $Q_{22} = 4$ $Q_{22} = 9$
88	COG $\neq 000-360$ COG = $\Delta\Delta\Delta$	Correct manually and $Q_{23} = 5$, otherwise $Q_{23} = 4$ $Q_{23} = 9$
89	SOG $\neq 00 - 99$ SOG = $\Delta\Delta$ SOG > 33	Correct manually and $Q_{24} = 5$, otherwise $Q_{24} = 4$ $Q_{24} = 9$ Correct manually and $Q_{24} = 5$, otherwise $Q_{24} = 3$
90	SLL $\neq 00-99$ SLL = $\Delta\Delta$ SLL > 40	Correct manually and $Q_{25} = 5$, otherwise $Q_{25} = 4$ $Q_{25} = 9$ Correct manually and $Q_{25} = 5$, otherwise $Q_{25} = 3$
91	$s_L \neq 0,1$	Correct manually and $Q_{27} = 5$, otherwise $Q_{27} = 4$
92	hh $\neq 00 - 99$ hh = $\Delta\Delta$ hh ≥ 13 hh < -01	Correct manually and $Q_{27} = 5$, otherwise $Q_{27} = 4$ $Q_{27} = 9$ Correct manually and $Q_{27} = 5$, otherwise $Q_{27} = 3$ Correct manually and $Q_{27} = 5$, otherwise $Q_{27} = 4$
93	RWD $\neq 000 - 360, 999$ RWD = $\Delta\Delta\Delta$	Correct manually and $Q_{28} = 5$, otherwise $Q_{28} = 4$ $Q_{28} = 9$
94	RWS $\neq 000 - 999$ RWS = $\Delta\Delta\Delta$ RWS > 110 kts	Correct manually and $Q_{29} = 5$, otherwise $Q_{29} = 4$ $Q_{28} = 9$ Correct manually and $Q_{29} = 5$, otherwise $Q_{29} = 3$
<u>RWD versus RWS</u>		
	RWD = 000, RWS $\neq 000$	Correct manually and Q_{28} or $Q_{29} = 5$, otherwise $Q_{28} = Q_{29} = 2$
	RWD $\neq 000$, RWS = 000	Correct manually and Q_{28} or $Q_{29} = 5$, otherwise $Q_{28} = Q_{29} = 2$

<u>Element</u>	<u>Error</u>	<u>Action</u>
<u>Specifications for setting quality control Indicators Q_1 to Q_{29}</u>		
0	No quality control (QC) has been performed on this element	
1	QC has been performed; element appears to be correct	
2	QC has been performed; element appears to be inconsistent with other elements	
3	QC has been performed; element appears to be doubtful	
4	QC has been performed; element appears to be erroneous	
5	The value has been changed as a result of QC	
6	The original flag is set "1" (correct) and the value will be classified by MQCS as inconsistent, dubious, erroneous or missing	
7	The original flag is set "5" (amended) and the value will be classified by MQCS as inconsistent, dubious, erroneous or missing	
8	Reserve	
9	The value of the element is missing	

APPENDIX I.16

(see paragraph 5.6.4.3)

HISTORICAL SEA-SURFACE TEMPERATURE (HSST) DATA EXCHANGE FORMAT

CD	MSQ	Q	LAT	LON	YR	MO	DA	HR	WIND DIRECT	WIND SPD	AIR TEMP	SEA TEMP	AREA
XXX	XXX	X	XXX	XXXX	XXX	XX	XX	XX	iXX	iXXX	XXX	XXX	XXXX

Field	Column	Element *
001	1-3	Card deck number in TDF-11
002	4-6	Marsden 10° square
003	7	Quadrant
004	8-10	Latitude
005	11-14	Longitude
006	15-17	Year (last three digits, i.e. 927 = 1927)
007	18-19	Month
008	20-21	Day
009	22-23	Hour - UTC
010	24-26	Wind direction and indicator
011	27-30	Wind speed and indicator
012	31-33	Air temperature
013	34-36	Sea-surface temperature
014	37-40	Area

* TDF-11 describes elements
 Logical rec. = 40
 Blocking factor = 100

*

* *

HSST Data Set - Extended format for Atlantic and Indian Oceans and Mediterranean Data

CHARACTER UK/US	NOTATION NL/DL	RECORD IDENTIFIER	
1		H	Historical Marine Data
2		M	
3		D	
4			Identifies the origin of the tape
5			
6	1		Octant
7	2		
8	3		Square number
9	4		
10	5		Month
11	6		
12	7		Year
13	8		
14	9		
15	10		Latitude
16	11	Position	
17	12	Unit and tenths	Longitude
18	13		
19	14		
20	15		Day of month
21	16		
22	17		Hour of day (00-23 UTC)
23	18	+, -	
24	19		
25	20		Sea temperature (tenths of °C)
26	21		
27	22	+, -	
28	23		
29	24		Air temperature (tenths of °C)
30	25		
31	26	+, -, e	e = Ice
32	27		
33	28		Wet-bulb temperature (tenths of °C)
34	29		
35	30		
36	31		Wind direction (whole degrees) 000 = calm
37	32		990 = variable
			999 = missing
38	33		
39	34		Wind speed (tenths of m/s)
40	35		
41	36		
42	37		
43	38		Barometric pressure (tenths of hPa)
44	39		
45	40		
46	41		Total cloud amount (oktas)
47	42		Flags for sea temperature
48	43		Flags for air temperature
49	44		Flags for wind
50	45	F sus 1	
51	46	F sus 2	Flags for suspect values

Codes for flag characters

Flags for sea temperatures and state of wet bulb

F sea

- 0 Sea temperature measured to 0.1°F accuracy
- 1 Sea temperature measured to 0.1°C accuracy
- 2 Sea temperature measured to 0.5°F accuracy
- 3 Sea temperature measured to 0.5°C accuracy
- 4 Sea temperature measured to 1°F or 1°C accuracy
- 5)
- 6) As for codes 0-4, but also the wet bulb is not frozen,
- 7) even when showing temperature below freezing point
- 8)
- 9)

Flags for dry-bulb and wet-bulb temperatures

F air

- 0 Air temperatures measured to 0.1°F accuracy
- 1 Air temperatures measured to 0.1°C accuracy
- 2 Air temperatures measured to 0.5°F accuracy
- 3 Air temperatures measured to 0.5°C accuracy
- 4 Air temperatures measured to 1°F or 1°C accuracy
- 5)
- 6) As for codes 0-3, but temperatures were measured by an
- 7) aspirated or whirling psychrometer
- 8)
- 9 Original units of temperature or accuracy unknown

Flags for wind observations

- 0 360 point compass
- 1 36 point compass
- 2 32 point compass Wind speed measured
- 3 16 point compass
- 4 8 point compass
- 5)
- 6) As for codes 0-4, but wind speed estimated or converted
- 7) from Beaufort force, or method of observation unknown
- 8)
- 9)

Flags for suspect values of sea temperature, air temperature and wind

F sus 1

- 0 No suspect element
- +1 Sea temperatures > 97°F (36.1°C)
- +2 Dry bulb or wet bulb not in range -5°F to 99.9°F (-20.5°C to 37.7°C) or wet bulb > dry bulb
- +4 Wind direction 990 (variable) and wind speed > 5 kt

Flags for suspect values of pressure and cloud amount

F sus 2

- 0 No suspect pressure or cloud amount
- +1 Pressure < 940 or > 1050 (pressures < 800 or > 1080 have been rejected)
- +2 Cloud amount not reported
- +4 Additional observation at the same time in the same 1° square, though not identical

The values of F sus 1 and F sus 2 may also be 3, 5, 6 or 7. This means that more than one value is suspect, and the code figures have been added together for the suspect values.

2) MODIFICATIONS TO THE GUIDE TO MARINE METEOROLOGICAL SERVICES – WMO NO. 471

Note: The changes proposed by the ETMC to WMO No. 471 appear in track changes below.

CHAPTER 3

MARINE CLIMATOLOGY

3.1 Introduction

Preparation of climatological charts and atlases for oceans became possible in the second half of the nineteenth century when ships' observations, recorded in special meteorological logbooks, started to become available in rapidly increasing numbers. For over 100 years these charts and atlases mainly for use by shipping were prepared nationally, obliging countries to ask for observations stored in other countries to supplement their own data sets.

The proposal for international exchange of marine data and for the preparation of marine climatological summaries originated at the third session of JCOMM (formerly CMM) in 1960 and was finally adopted by Fourth Congress in 1963. The objective was to establish a joint effort of all maritime nations in the preparation and publication of climatological statistics and charts for the oceans. The underlying idea was that all observations collected from ships of whatever nationality should be included. Eight countries, each with a specific ocean area of responsibility, were designated to process the data in prescribed forms and regularly publish the climatological summaries.

To improve the flow of the observational data, JCOMM at its eleventh session in 1993 decided on the establishment of two Global Collecting Centres and this decision was ratified by Executive Council at its forty-fifth Session in 1993.

Marine climatology today supports transportation, engineering and the basic and applied sciences with data and information about the environment from tens of metres below, to tens of metres above the sea surface. Growing interest in studies of climate change and air-sea interaction have increased the demand for marine climatological data. A comprehensive account of the uses of marine climatology can be found in the *Guide to the Applications of Marine Climatology* (WMO-No. 781), and in its Dynamic Part, *Advances in the Applications of Marine Climatology* (WMO/TD-No. 1081).

The basic sources of data are ships, buoys, satellite, aircraft and a few other specialized sensing systems such as land-based radar. New technology is having a significant impact on the traditional methods in marine climatology. Telecommunications advances have led to an increase in the amount of data captured automatically and a decrease in manual key entry requirements. High-density computer readable media is now the standard method of data exchange. Computers allow for automated quality control and data validation. Automation in analysis and mapping allows derived quantities such as heat, heat flux, wind stress and atmospheric refractivity to be computed from operationally available data. Data can be used in computer models to generate fields, e.g. of sea-surface temperature, pressure and wind. As well as provision on paper-based media, data can also be provided on computer readable media for analysis on personal computers. Advances in computer technology allow a vast amount of data to be provided on one disc and the data can be displayed in chart, map or graphic form.

3.2 Marine climatological summaries

3.2.1 General

The establishment of the international exchange and processing arrangements described above for the 'Marine Climatological Summaries Scheme', as it is called, required the cooperation of all maritime countries participating in the WMO Voluntary Observing Ships' Scheme, i.e. those which

have recruited Selected, VOSclim, Supplementary or Auxiliary ships (see Chapter 6 of this *Guide*). More information about the Marine Climatological Summaries Scheme can be found on the GCC website (http://www.metoffice.gov.uk/weather/marine/observations/gathering_data/gcc.html) or (<http://www.dwd.de/gcc>), whilst more information about the VOS Scheme can be found on the VOS website (<http://www.bom.gov.au/jcomm/vos/>).

In this scheme the oceans and seas are divided into areas of responsibility and eight Members (known as Responsible Members) assumed responsibility to prepare marine climatological summaries without cost to WMO. Data from fixed ship stations within the area are also included. In order to prepare these summaries, the Global Collecting Centres supply Responsible Members surface observations in an internationally accepted format from all Members operating voluntary observing ships and/or (historically) fixed ship stations in their respective areas of responsibility.

The international procedures governing the Marine Climatological Summaries Scheme have the status of Technical Regulations within WMO and are included in the *Manual on Marine Meteorological Services* (WMO-No. 558), Volume I, Part I, Section 5.

3.2.2 Members responsible for the preparation of summaries

The Responsible Members and the areas allotted to them are shown in Annex 3.A to this Chapter. The boundaries of the areas of responsibility are kept under review by JCOMM. Adjustments, however, should be kept to a minimum.

Climatological summaries shall optionally be prepared for a number of small areas called 'representative areas', and (historically) for fixed ship stations within the assigned area of responsibility. The representative areas were selected on the basis of the density of available data, climatic gradients and factors such as the position of fixed ship stations and island stations. There is a reasonable distribution of representative areas according to all areas of responsibility. An example of the representative areas in one area of responsibility is shown in Annex 3.B to this Chapter. The Area Indices System is also explained in Annex 3.B.

Responsible Members are represented on the Expert Team on Marine Climatology, under JCOMM's Data Management Coordination Group, which keeps the Marine Climatological Summaries Scheme under review, particularly with regard to the rapidly changing technology in the processing, storage and supply of large volumes of data.

3.2.3 Global Collecting Centres (GCCs)

Two Responsible Members (Germany and the United Kingdom) operate Global Collecting Centres (GCCs), which receive ships' observations from all Members with VOS fleet. These two centres are maintained in parallel so that the data set will still be available in the event of some catastrophe happening at one Centre.

GCCs ensure that minimum quality control has been applied to the data, and then supply, every three months, data to the Responsible Members relevant to each one's area of responsibility. They will also provide a global data set to those Responsible Members who wish to receive it.

3.2.4 The flow of observational data

Marine meteorological observations are recorded onboard most ships in special meteorological logbooks typically provided by National Meteorological and Hydrological Services (NMHSs). The Members operating voluntary observing ships and/or (historically) fixed ship

stations, so-called Contributing Members, should arrange for the provision of a suitable meteorological logbook, which can be in hard-copy or electronic format. Details of the layout of the hard-copy logbook are to be found in Chapter 6, paragraph 6.8.1 of this *Guide*.

The observations are transferred from the hard-copy logbooks to a computer-compatible medium, in a standard internationally agreed format. Every effort should be made to apply minimum quality control to the data. Details of this transfer and associated quality control are to be found in paragraphs 3.2.8 and 3.2.9 below.

An increasing number of ships are being equipped with a personal computer and software which stores the observations on computer readable media in the internationally agreed format. This avoids a source of possible errors in the manual data transfer from logbook to the computer-compatible medium.

The data are then sent to both GCCs, i.e. two copies of each data set are required, one for each centre. The data should be dispatched at three-monthly intervals. The Member sending the data should notify the GCCs of the dispatch of the data and provide details of the order in which the data are sorted.

3.2.5 Preparation of marine climatological summaries

The detailed procedures for the preparation of marine climatological summaries are described in the *Manual on Marine Meteorological Services* (WMO-No. 558), Volume I, Part I, Section 5.3. Summaries shall optionally be prepared in both tabular and chart form and normally include air and sea surface temperature, dew-point temperature, visibility, weather, wind direction and speed, atmospheric pressure, clouds and waves. A necessary minimum number of observations is specified before a mean can be calculated for a given area. Routine publication of annual summaries ceased in 1981, although they are available on request and Responsible Members may still publish them if they wish. Decadal climatological summaries shall optionally be prepared for each decade 1961-70, 1971-80, 1981-90, etc.

3.2.6 Availability of summaries and observational data

Responsible Members keep the Secretariat informed of the availability of their marine climatological data and published summaries so that an inventory can be compiled annually and circulated to Members for information.

Responsible Members will make available, on request, copies of the data at the cost of copying. The data will be on computer readable media in the international exchange format, unless another format has been agreed between the requesting and Responsible Members.

Requests for marine climatological summaries or for observational data should be addressed directly to the Responsible Member concerned and not to the Secretariat.

3.2.7 Data exchange formats

It is essential to use standard data formats to facilitate international exchange of data for climatological purposes, particularly when so much of the processing is automated. The standard format for provision of data to Responsible Members is the International Maritime Meteorological Tape (IMMT) format. Any form of data exchange on computer readable media may be used provided the format of the data complies with the details as set out in Annex 3.C to this Chapter. The technology for data transfer is changing rapidly and the means of data exchange needs to keep up with the current technology.

A second format which may be used for national and bilateral exchange of data is set out in Annex 3.D. Any alternative format must only be used by mutual agreement between the two

Members which are exchanging data.

Members wishing to exchange their observational data on other computer readable media or in print-outs in the case of very small numbers of observations should arrange for their exchange on a bilateral basis.

3.2.8 Assembly and Exchange of Historical Marine Data

Because of the importance of the sea temperature in climatic change, the Historical Sea Surface Temperature (HSST) Data Project compiled a comprehensive, homogeneous set of sea surface temperature data for the period from 1861 to 1960 (i.e. for the century preceding the beginning of the Marine Climatological Summaries Scheme). The results can be consulted in the *User's Guide to the Data and Summaries of the Historical Sea Surface Temperature Data Project* (MMROA Report No. 13, WMO/TD-No. 36, 1985).

However in the decades since completion of the HSST Data Project, projects such as the International Comprehensive Ocean-Atmosphere Data Set (ICOADS) have undertaken to build on that work, by assembling additional international historical ship (and other) records from a variety of sources, quality controlling the data, and making the observations and associated gridded products openly available to the international user community. This is now the responsibility of WMO-IOC Centres for Marine Meteorological and Oceanographic Climate Data (CMOCs) to assemble historical marine and oceanographic climate data.

Members with historical data which have not been included in the original HSST Data Project or in ICOADS or CMOCs, should send those data to GCCs in the IMMT format – and the GCCs will ensure their provision to CMOCs (or ICOADS). The data should be accompanied by documentation describing the source of the data, the precision of the original observations and conversion algorithms. For example, if the original observations recorded the visibility as poor, moderate, or good, an explanation is needed on how these terms are expressed in distances of kilometres.

3.2.9 Quality Control

3.2.9.1 GENERAL

The accuracy of data is of primary importance to climatological computations and scientific investigations. It is essential that marine data are quality controlled before exchange. Quality control consists of checking of the content, including identification groups, of observational data to ensure its accuracy. Quality control procedures for climatological data in general are described in the *Guide to Climatological Practices* (WMO-No. 100). Quality control has been incorporated in WMO's CLICOM (CLimate COMputing) programme and can be used for small marine data sets. A discussion of quality control of marine data can be found in Chapter 3 of *Guide to the Applications of Marine Climatology* (WMO-No. 781).

However, errors can occur when:

- (a) Misreading an on board instrument, a sensor malfunction, or in entering the observation in the logbook;
- (b) Transcribing the data on to computer readable media.

In the event that data are taken from SHIP reports on the GTS, errors can arise in transmission.

3.2.9.2 MINIMUM QUALITY CONTROL

The primary responsibility for the quality control of data rests with the NMHS where the data originated. All Members should make every effort to apply the minimum quality control procedures described in Annex 3.E before dispatching the data to the GCCs. This quality control includes checks that the observation of catch element is within the possible range, and that the change in position between observations is within reasonable limits, and that call sign and country code have been included. There is space in the IMMT format for quality control flags. These indicators show whether the element that has been flagged is doubtful or whether it has been corrected. A problem which often arises is deciding whether an observation is an error or an actual extreme value. Generally care should be exercised in correcting doubtful values; suspect observations may be real extremes of special meteorological interest.

Nevertheless, it is stressed that, while flagging data as doubtful is an accepted procedure, all efforts should first be made to correct those data.

Meteorological logbooks can be scrutinized manually before data transfer to eliminate obvious observational and recording errors. However the minimum quality control should be carried out after transfer to computer readable media to allow for transcription errors. The quality control is best carried out automatically by computer and software are available for this purpose. Minimum quality control software is available from GCCs upon request or from the WMO (http://www.wmo.int/pages/prog/amp/mmop/mqc_soft.html).

It is of the utmost importance that Members should make adequate provision for quality control of data to ensure that they are as free from error as possible. GCCs ensure that this minimum quality control has been carried out and that further quality control may be applied to the data by the Responsible Members.

3.3 Special marine climatological information

In addition to the elements in the IMMT format which can be used in the production of standard marine climatological summaries, there are other observations of interest to many marine interests. Two specific observation systems which have been instituted relate to freak waves and to sea surface current data.

3.3.1 *Report of freak waves*

The occurrence of unusual waves and the occasional distress to vessels that may follow has been noted at times over many years, but accurate observations are rare. A freak wave may be defined as a wave of very considerable height ahead of which there is a deep trough. It is the unusual steepness of the wave which is its outstanding feature and which makes it dangerous to shipping. All marine observers, at fixed or mobile stations, are encouraged to observe and report any such occurrences.

Guidelines for reporting freak waves can be found in Chapter 6, Annex 6.C of this *Guide*. Procedures for the dealing with reports of freak waves are given in the *Manual on Marine Meteorological Services*, Volume I, Part I, Section 6.2.1

3.3.2 *Special techniques for other parameters*

Requirements arise for information on other parameters, or for more detailed analyses of some parameters included above. Waves are among the most complex and important elements at the surface of the sea. In addition to visual observations from ships, they can be measured by wave recorders on fixed platforms. Wave climatologies are often derived by means of hindcasts, whereby all available historical data (predominantly wind data) is re analysed for input into suitable wind and wave computer models for calculation of the wave characteristics. More information on

these techniques can be found in the *Guide to Wave Analysis and Forecasting* (WMO No. 702) and in the *Guide to the Applications of Marine Climatology* (WMO No. 781).

The extreme value of elements such as wind, wind gusts and waves is of great interest for coastal engineering and there are statistical means of estimating the extreme value from a set of observations. However the problem is that in an extreme weather event, sensors are often destroyed or damaged, while the feedback signal to a satellite is so attenuated that it is impossible to determine a reliable extreme value. Thus a set of observations may not indicate the true extremes which have been experienced.

Sea surface temperature, radiant flux, cloud and some wind data can be extracted from special satellite data sets. A far greater coverage of sea surface temperature data can be obtained by satellite than from ships which mostly travel regular shipping lanes. However, observations from ship and from satellite are not directly compatible. The satellite measures the temperature of the very top of the sea, the ship measures the temperature from a few centimetres down to several metres. The two measurements can be very different, particularly in calm weather. Special techniques have been developed to homogenize the two types of observation.

The requirement for a climatology of some elements, required more for global climate studies than marine purposes alone, is not yet able to be satisfied, e.g. for precipitation over the ocean.

3.4 Presentation of climatological data

3.4.1 General

Climatological data can be presented in many different forms. They can be shown as long term averages or as mean values for particular months. They usually include frequencies of occurrence of extremes or other values which are thought to be critical with respect to particular operations. Analyses can disclose statistical relationships between parameters such as wind speed and direction, wave height and period, fog and air/sea temperature difference, etc. Optimum time and space scales are often dictated by the necessary statistical tests for homogeneity of data applied with a realistic understanding of the requirements. Even so, the factor of data availability often forces compromise. Automated treatment of marine data allows the objective production of analysed charts and gridded data fields. This allows easier compilation of climatological summaries over greater time spans. A comprehensive treatment of the analysis, presentation and interpretation of marine climatological data can be found in the *Guide to the Applications of Marine Climatology* (WMO No. 781).

Marine data comes from many varied sources and periods from varied instruments. Care needs to be taken in the combination of data from varied sources, and prime attention must be given to consistency and continuity, and to scrutiny of historical data, especially when long periods are being considered. Care must be taken with the combination of standard and non-standard period statistics, as well as with the use of satellite, buoy and ocean weather station data as reference levels or with extrapolation into data sparse regions.

3.4.2 Climatological charts

The layout for marine climatological summary charts for representative areas is shown in the *Manual on Marine Meteorological Services*, Volume I, Part I, Appendix I.9. There are many other ways of displaying the data in chart form, and several NMHSs have published marine climatological charts and atlases based on data observed in periods since 1860. These charts were prepared primarily to serve marine navigation, but contain useful information for fisheries and

other marine operations. Data are usually presented for individual months as an average over the entire period for which data were available. The Mercator projection basis usually been used, but others may be employed for special requirements. These charts may also include numerical data, graphs, isopleths and other additional data presentation. Elements covered by these charts may include, among others:

- (a) Surface wind: Frequency distribution of wind speeds on the eight points of the compass (wind rose); wind directions, mean vector of wind speed and prevailing wind direction; frequencies of light winds, gales and storms; bivariate normal statistics;
- (b) Surface currents: The same presentation as for wind, including frequencies of currents exceeding certain speeds;
- (c) Waves (sea and swell): Wave charts of frequencies of total wave height, usually the higher or a combination of sea and swell. Swell charts depict frequencies of short, medium and long swell in four or eight directions (compass points). Wave charts based on data observed since 1949 (when a new code allowed more detail to be given in ships' observations of waves) give frequencies of waves exceeding given height limits in various directions and sometimes also indications of wave periods;
- (d) Visibility: Frequencies of visibility of less than 1 km (fog) and other ranges;
- (e) Precipitation and cloud cover: Precipitation given as frequencies or percentages of the number of bouts during which precipitation was observed. Frequencies of various degrees of cloud cover (total and low) and heights;
- (f) Temperatures, air and sea surface: Isotherms at regular intervals, mean values and standard deviations of the frequency distribution for small areas; percentage occurrence of critical threshold values;
- (g) Humidity: Mean values of dew point temperature; various statistics involving relative humidity, wet bulb and dew point;
- (h) Air pressure; pressure systems: Isobars and, on some atlases, frequencies of deep extratropical cyclones with depiction of storm tracks;
- (i) Tropical cyclones: Frequencies of occurrence, tracks of individual cyclones, distribution for the months of the year, intensities and intensity changes during the life history of a cyclone;
- (j) Sea ice and icebergs: The geographical distribution of different types of sea ice and of icebergs for each month, charts of probability of various positions of ice edge and boundaries of ice patterns with different ice compactness, ice convergence and divergence zones;
- (k) Derived quantities: Heat flux, transport data, refractivity, superstructure icing potential, atmospheric stability.


3.4.3 Atlases and CD-ROMs

Modern computer technology allows a vast amount of data to be provided on one computer compatible media and the data can be displayed in chart, map or graphic form. CD-ROMs are becoming available which display marine climatological data in at least some of the ways described in paragraph 3.4.2 above.

ANNEX 3.A

AREAS OF RESPONSIBILITY AND RESPONSIBLE MEMBERS FOR CLIMATOLOGICAL SUMMARIES

(Reference paragraph 3.2.2)




*The Russian Federation is responsible for the compilation of a complete data set and shall optionally be responsible for the preparation of the summaries for the sea routes.

ANNEX 3.B


AN EXAMPLE OF A SELECTED REPRESENTATIVE AREA INCLUDED IN THE MARINE CLIMATOLOGICAL SUMMARIES

(Reference paragraph 3.2.2)

a. The Indian Area of Responsibility



AREAS INDICES SYSTEM FOR MARINE CLIMATOLOGICAL SUMMARIES



Representative area	A	shall be coded	:	00037
"	"	B	"	01288
"	"	C	"	51281
"	"	D	"	81288
"	"	E	"	80187
"	"	F	"	31149

The following area indices systems shall be used:

- A selected representative area shall be indicated with reference to the position in the area of the 1-degree square corner which is nearest (1) to the Equator and (2) to the Greenwich meridian, in that sequence;
- A five-figure code shall be used for "area index";
- The first figures of the code - QL_aL_o - shall indicate the 10-degree square in which this 1-degree square is situated, where:
 - The first figure shall be octant (code 3300);
 - The second figure shall be tens of the latitude of the 10-degree square;
 - The third figure shall be the tens of the longitude of the 10-degree square.
- The fourth and fifth figures of the code shall be the number of the 1-degree square within the 10-degree square as indicated in the above figure.

ANNEX 3.C

AMENDMENTS TO THE *MANUAL ON MARINE METEOROLOGICAL SERVICES* (WMO-No. 558) AND *GUIDE TO MARINE METEOROLOGICAL SERVICES* (WMO-No. 471)

**LAYOUT FOR THE INTERNATIONAL MARITIME METEOROLOGICAL TAPE (IMMT) FORMAT
IMMT-5 (Version 5)**

Notes:

- (a) The representation for missing data in any field is all blank(s).
- (b) Many of the "Codes" in the IMMT format match "symbolic letters" as defined in the *Manual on Codes* (WMO-No.306) for the traditional alphanumeric (e.g. FM 13) SHIP code. However, the elements added for the VOSclim project (as introduced for IMMT-2), for example, did not appear in WMO-No.306, thus an effort was made to select unique new Codes to avoid conflicts in meaning between symbolic letter groups in WMO-No.306 versus Codes defined only in IMMT.

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
1	1	i _T	Format/temperature indicator	3 – temperatures in tenths of °C 4 – temperatures in halves of °C 5 – temperatures in whole °C [Note: codes 1-2 were previously used to refer to the obsolete IMMPC format; current codes all refer to the IMMT format]
2	2-5	AAAA	Year UTC	Four digits
3	6-7	MM	Month UTC	01 – 12 January to December
4	8-9	YY	Day UTC	01 – 31
5	10-11	GG	Time of observation	Nearest whole hour UTC, WMO specifications
6	12	Qc	Quadrant of the globe	WMO code table 3333
7	13-15	L _a L _a L _a	Latitude	Tenths of degrees, WMO specifications
8	16-19	L _o L _o L _o L _o	Longitude	Tenths of degrees
9	20		Cloud height (h) and visibility (VV) measuring indicator	0 – h and VV estimated 1 – h measured, VV estimated 2 – h and VV measured 3 – h estimated, VV measured
10	21	h	Height of clouds	WMO code table 1600
11	22-23	VV	Visibility	WMO code table 4377
12	24	N	Cloud amount	Oktas, WMO code table 2700; show 9 where applicable
13	25-26	dd	True wind direction	Tens of degrees, WMO code table 0877; show 00 or 99 where applicable
14	27	i _w	Indicator for wind speed	WMO code table 1855
15	28-29	ff	Wind speed	Units of knots or meters per second,

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				hundreds omitted; values in excess of 99 knots are to be indicated in units of meters per second and i_w encoded accordingly; the method of estimation or measurement and the units used (knots or meters per second) are indicated in element 14. Wind is at observation height or anemometer height (i.e. it is not reduced to 10m).
16	30	s_n	Sign of temperature	WMO code table 3845
17	31-33	TTT	Air temperature	Tenths of degrees Celsius
18	34	s_t	Sign of dew-point temperature	0 – positive or zero measured dew-point temperature 1 – negative measured dew-point temperature 2 – iced measured dew-point temperature 5 – positive or zero computed dew-point temperature 6 – negative computed dew-point temperature 7 – iced computed dew-point temperature
19	35-37	$T_d T_d T_d$	Dew-point temperature	Tenths of degrees Celsius
20	38-41	PPPP	Air pressure	Tenths of hectopascals
21	42-43	ww	Present weather	WMO code table 4677 or 4680
22	44	W_1	Past weather	WMO code table 4561 or 4531
23	45	W_2	Past weather	WMO code table 4561 or 4531
24	46	N_h	Amount of lowest clouds	As reported for C_L or, if no C_L cloud is present, for C_M , in oktas; WMO code table 2700
25	47	C_L	Genus of CL clouds	WMO code table 0513
26	48	C_M	Genus of CM clouds	WMO code table 0515
27	49	C_H	Genus of CH clouds	WMO code table 0509
28	50	s_n	Sign of sea-surface temperature	WMO code table 3845
29	51-53	$T_w T_w T_w$	Sea surface temperature	Tenth of degrees Celsius
30	54		Indicator for sea-surface temperature measurement	0 – Bucket thermometer 1 – Condenser inlet 2 – Trailing thermistor 3 – Hull contact sensor 4 – "Through hull" sensor 5 – Radiation thermometer 6 – Bait tanks thermometer 7 – Others

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
31	55		Indicator for wave measurement	
			Shipborne wave recorder	0 – Wind sea and swell estimated 1 – Wind sea and swell measured 2 – Mixed wave measured, swell estimated 3 – Other combinations measured and estimated
			Buoy	4 – Wind sea and swell measured 5 – Mixed wave measured, swell estimated 6 – Other combinations measured and estimated
			Other measurement system	7 – Wind sea and swell measured 8 – Mixed wave measured, swell estimated 9 – Other combinations measured and estimated
32	56-57	P _W P _W	Period of wind waves or of measured waves	Whole seconds; show 99 where applicable in accordance with Note (3) under specification of P _W P _W in WMO–No.306.
33	58-59	H _W H _W	Height of wind waves or of measured waves	Half-meter values. Examples: Calm or less than ¼m to be encoded 00; 3¼m to be encoded 07; 7m to be encoded 14; 11½m to be encoded 23.
34	60-61	d _{W1} d _{W1}	Direction of predominant swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks = no observation of waves attempted.
35	62-63	P _{W1} P _{W1}	Period of predominant swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
36	64-65	H _{W1} H _{W1}	Height of predominant swell waves	Half-meter values (see under element 33)
37	66	I _s	Ice accretion on ships	WMO code table 1751
38	67-68	E _s E _s	Thickness of ice accretion	In centimeters
39	69	R _s	Rate of ice accretion	WMO code table 3551

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
40	70		Source of observation	0 – Unknown 1 – Logbook (paper) 2 – National Telecommunication channels 3 – National Publications 4 – Logbook (electronic) 5 – Global Telecommunication channels (GTS) 6 – International Publications [Note: Formerly (usage now discontinued): codes 1-3 also referred to “National data exchange,” and codes 4-6 also referred to “International data exchange”; distinction added between paper and electronic logbook]
41	71		Observation platform	0 – Unknown 1 – Selected ship 2 – Supplementary ship 3 – Auxiliary ship 4 – Registered VOSClm ship 5 – Fixed sea station (e.g., rig or platform) 6 – Coastal station [Note: 7 – Reserved] [Note: 8 – Reserved] 9 – Others/data buoy [Note: Formerly (usage now discontinued): code 4 referred to “Automated station/data buoy,” and codes 7-8 referred to “Aircraft” and “Satellite,” respectively]
42	72-78		Ship's call sign	Ship's call sign stored left-justified (with right-blank fill) as follows: 7-character call sign: columns 72–78 6-character call sign: columns 72–77 5-character call sign: columns 72–76 4-character call sign: columns 72–75 3-character call sign: columns 72–74
43	79-80		Country which has recruited the ship	According to the 2-character alphabetical codes assigned by the International Organization for Standardization (ISO)
44	81		National use	
45	82		Quality control indicator	0 – no QC has been performed 1 – manual QC only 2 – automated QC only (such as using only MQC) 3 – automated QC only (with time sequence checks) 4 – manual and automated QC (superficial) 5 – manual and automated QC (superficial; with time-sequence checks) 6 – manual and automated QC (intensive; with time-sequence checks) 7 – [reserved] 8 – [reserved] 9 – national system of QC (information to be furnished to WMO)

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>	
46	83	i _x	Weather data indicator	1 – Manual	
				4 – Automatic	If present and past weather data included Code tables 4677 and 4561 used
				7 – Automatic	If present and past weather data included Code tables 4680 and 4531 used
47	84	i _R	Indicator for inclusion or omission of precipitation data	WMO code table 1819	
48	85-87	RRR	Amount of precipitation which has fallen during the period preceding the time of observation, as indicated by t _R	WMO code table 3590	
49	88	t _R	Duration of period of reference for amount of precipitation, ending at the time of the report	WMO code table 4019	
50	89	s _w	Sign of wet-bulb temperature	0 – positive or zero measured wet-bulb temperature 1 – negative measured wet-bulb temperature 2 – iced measured wet-bulb temperature 5 – positive or zero computed wet-bulb temperature 6 – negative computed wet-bulb temperature 7 – iced computed wet-bulb temperature	
51	90-92	T _b T _b T _b	Wet-bulb temperature	In tenths of degree Celsius, sign given by element 50	
52	93	a	Characteristic of pressure tendency during the three hours preceding the time of observation	WMO code table 0200	
53	94-96	ppp	Amount of pressure tendency at station level during the three hours preceding the time of observation	In tenths of hectopascal	
54	97	D _s	True direction of resultant	WMO code table 0700	

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
			displacement of the ship during the three hours preceding the time of observation	
55	98	v_s	Ship's average speed made good during the three hours preceding the time of observation	WMO code table 4451
56	99-100	$d_{W2}d_{W2}$	Direction of secondary swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks – no observation of waves attempted.
57	101-102	$P_{W2}P_{W2}$	Period of secondary swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
58	103-104	$H_{W2}H_{W2}$	Height of secondary swell waves	Half-meter values (see under element 33)
59	105	c_i	Concentration or arrangement of sea ice	WMO code table 0639
60	106	S_i	Stage of development	WMO code table 3739
61	107	b_i	Ice of land origin	WMO code table 0439
62	108	D_i	True bearing of principal ice edge	WMO code table 0739
63	109	z_i	Present ice situation and trend of conditions over the preceding three hours	WMO code table 5239
64	110		FM code version	0 – previous to FM 24-V 1 – FM 24-V 2 – FM 24-VI Ext. 3 – FM 13-VII 4 – FM 13-VIII 5 – FM 13-VIII Ext. 6 – FM 13-IX 7 – FM 13-IX Ext. 8 – FM 13-X 9 – FM 13-XI A – FM 13-XII Ext. B – FM 13-XIII C – FM 13-XIV Ext. [Note: etc. for future configurations]
65	111		IMMT version	0 – IMMT version just prior to version number being included 1 – IMMT-1 (in effect from 2 Nov. 1994) 2 – IMMT-2 (in effect from Jan. 2003)

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				3 – IMMT-3 (in effect from Jan. 2007) 4 – IMMT-4 (in effect from Jan. 2011) 5 – IMMT-5 (in effect from June 2012) [Note: etc. For future configurations]
66	112	Q ₁	Quality control indicator for (h)	0 – no QC has been performed on this element 1 – QC performed; element appears correct 2 – QC performed; element appears inconsistent with other elements 3 – QC performed; element appears doubtful 4 – QC performed; element appears erroneous 5 – QC performed; element changed (possibly to missing) as a result 6 – QC flag amended: element flagged by CM as correct (1), but according to MQCS still appears suspect (2-4) or missing (9) 7 – QC flag amended: element flagged by CM as changed (5), but according to MQCS still appears suspect (2-4) 8 – [reserved] 9 – element is missing
67	113	Q ₂	QC indicator for (VV)	- idem -
68	114	Q ₃	QC indicator for (N and clouds: elements 12, 24–27)	- idem -
69	115	Q ₄	QC indicator for (dd)	- idem -
70	116	Q ₅	QC indicator for (ff)	- idem -
71	117	Q ₆	QC indicator for (s _n and TTT)	- idem -
72	118	Q ₇	QC indicator for (s _t and T _d T _d T _d)	- idem -
73	119	Q ₈	QC indicator for (PPPP)	- idem -
74	120	Q ₉	QC indicator for (weather: ww, W ₁ , W ₂ ; elements 21–23)	- idem -
75	121	Q ₁₀	QC indicator for (s _n and T _w T _w T _w)	- idem -
76	122	Q ₁₁	QC indicator for (P _w P _w)	- idem -
77	123	Q ₁₂	QC indicator for (H _w H _w)	- idem -
78	124	Q ₁₃	QC indicator for (swell: elements 34–36, 56–58)	- idem -

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
79	125	Q ₁₄	QC indicator for (i _R RRRt _R)	- idem -
80	126	Q ₁₅	QC indicator for (a)	- idem -
81	127	Q ₁₆	QC indicator for (ppp)	- idem -
82	128	Q ₁₇	QC indicator for (D _s)	- idem -
83	129	Q ₁₈	QC indicator for (v _s)	- idem -
84	130	Q ₁₉	QC indicator for (s _w and T _b T _b T _b)	- idem -
85	131	Q ₂₀	QC indicator for ships' position	- idem -
86	132	Q ₂₁	Version identification for Minimum Quality Control Standard (MQCS)	1 – MQCS-1 (Original version, Feb. 1989): CMM-X 2 – MQCS-2 (Version 2, March 1997) CMM-X 3 – MQCS-3 (Version 3, April 2000) SGMC-V 4 – MQCS-4 (Version 4, June 2001): JCOMM 5 – MQCS-5 (Version 5, July 2004): ETMC-I 6 – MQCS-6 (Version 6, November 2009) JCOMM-III 7 = MQCS-VII (Version 7, in effect from June 2012) JCOMM-IV [Note: etc. for future configurations]
87	133-135	HDG	Additional Requirements for VOSCLim: Ship's heading; the direction to which the bow is pointing, referenced to true North	(001-360); e.g. 360 = North 090 = East
88	136-138	COG	Ship's ground course; the direction the vessel actually moves over the fixed earth and referenced to True North	(000-360); e.g. 360 = North 000 = No Movement 090 = East
89	139-140	SOG	Ship's ground speed; the speed the vessel actually moves over the fixed earth	(00-99); Round to nearest whole knot
90	141-142	SLL	Maximum height in meters of deck cargo above Summer maximum	(00-99); Round to nearest whole meter

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
			load line (reference level)	
91	143	s _L	Sign of departure of reference level	0 = positive or zero, 1 = negative
92	144- 145	hh	Departure of reference level (Summer maximum load line) from actual sea level	Difference to the nearest whole meter (00-99) between the Summer maximum load line and the sea level (water line); positive when the Summer maximum load line is above the level of the sea and negative if below the water line
93	146- 148	RWD	Relative wind direction in degrees off the bow	Relative wind direction; e.g. 000 = no apparent relative wind speed (calm conditions on deck). Reported direction for relative wind = 001-360 degrees in a clockwise direction off the bow of the ship. When directly on the bow, RWD = 360.
94	149- 151	RWS	Relative wind speed indicated by i _w (knots or m s ⁻¹)	Reported in either whole knots or whole meters per second (e.g. 010 knots or 005 m s ⁻¹). Units established by i _w (element 14) [Note: RWS is a 3-character field to store values of RWS larger than ff (if i _w indicates knots), e.g. ff=98 knots, RWS=101 knots; see also element 15.] [Note: coding as for element 66]
95	152	Q ₂₂	QC indicator for (HDG)	– idem –
96	153	Q ₂₃	QC indicator for (COG)	
97	154	Q ₂₄	QC indicator for (SOG)	
98	155	Q ₂₅	QC indicator for (SLL)	
	156		blank	[Note: Formerly (usage now discontinued): QC indicator for (s _L); now Q ₂₇ serves as the indicator for both s _L and hh]
99	157	Q ₂₇	QC indicator for (s _L and hh)	– idem –
100	158	Q ₂₈	QC indicator for (RWD)	– idem –
101	159	Q ₂₉	QC indicator for (RWS)	– idem –
102	160- 163	RH	Relative humidity	Tenths of Percentage
103	164	RHi	Relative humidity indicator	0 – Relative humidity in tenths of Percentage, measured and originally reported 1 – Relative humidity in whole Percentage, measured and originally reported [Note: 2 – Reserved] 3 – Relative humidity in tenths of

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
104	165	AWSi	AWS indicator	Percentage, computed 4 – Relative humidity in whole Percentage, computed 0 – No Automated Weather Station (AWS) 1 – AWS 2 – AWS plus Manual Observation
105	166- 172	IMOno	IMO number	Seven digits (or left justified with right-blank fill)

3) MODIFICATION PROPOSED TO THE INTERNATIONAL LIST OF SELECTED, SUPPLEMENTARY AND AUXILIARY SHIPS – WMO NO. 47

Summary

The sixth session of the Ship Observations Team (SOT, 11-15 April 2011, Hobart, Australia) endorsed recommendations from the Task Team on Metadata for WMO Publication No. 47 (TT-Pub47) to introduce structural changes to the format of WMO Publication No. 47 (Pub 47).

The changes are (1) modification to the field type and definition of the existing metadata element **prST**, and (2) the addition of a new metadata element **spd**.

These changes will necessitate a new version (version 4.0) of Pub 47, coinciding with the adoption of a new XML Schema definition and new CSV format for reporting the data.

Background

prST

The TT-Pub47 and the Task Team on Satellite Communications (TT-Satcoms), jointly recommended at SOT-6 the use of a non-mandatory list of telecommunication methods for reporting how the ship sends the weather reports. Members were invited to use this non-mandatory table in lieu of “free form” text in metadata element **prST** (current description = Satellite system for transmitting reports). The selection of a standard reporting method from a defined list will enable the TT-Satcoms to more accurately report on the communication methods, and trends, used by ships to transmit their weather observations.

spd

The TT-Pub47, in response to a request from the monitoring centres, recommended a new metadata element to assist with the monitoring and tracking of ships. The metadata element **spd** (proposed description = Maximum operating speed of the vessel on normal service) will enable monitoring centres to compare the calculated speed of a ship between successive observations against the maximum speed of the ship and declare a position suspect if the calculated value exceeds the quoted maximum value.

Discussion

The Team agreed:

1. to adopt a non-mandatory list of telecommunication methods for metadata element **prST** pending approval from JCOMM to change **prST** (proposed new description = Transmission system for sending weather reports) from a “free-form” text field to a mandatory table field.
 - a. The Team noted that changing the metadata element **prST** to a table field will require a companion footnote field for consistency with all other table fields.
2. to introduce a new metadata element **spd** (proposed description = Maximum operating speed of the vessel on normal service).
 - a. The element will be reported in whole knots.

Recommendations

The SOT requests JCOMM to approve the following recommendations endorsed at SOT-6.

Subject to approval by JCOMM, the changes would be promulgated as a new version (version 4.0) of Pub47, with an implementation date of 1 January 2013.

Recommendation 1

The current metadata element **prST** (Satellite system for transmitting reports) is amended as follows:

- a. The definition shall be changed to **Transmission system for sending weather reports**.
- b. The element is changed from a “free-form” text field to a mandatory table field (**Code Table 1601**) with a companion footnote.
- c. The element **prST** is added to **Code Table 0601** (Code name of the field to which the footnote applies) which lists all metadata elements that have a footnote for reporting additional information.
- d. The initial list of telecommunication methods for metadata element **prST** is at attachment 1.

Recommendation 2

A new metadata element **spd** is added as follows:

- a. The definition of the metadata element shall be **Maximum operating speed of the vessel on normal service**.
- b. The element shall be reported in whole knots.

Recommendation 3

Modified metadata exchange formats are required to accommodate recommendation 1 and 2 as follows:

- a. The modified exchange formats will be referred to as version 4.0:
 - i The Pub 47 documentation will be amended to accommodate recommendation 1 and 2, and will be distributed as Pub 47 version 4.0.
- b. A new XML Schema is required to accommodate recommendations 1 and 2:
 - i The new XML Schema shall be named **v4pub47.xsd** to distinguish it from the current version 3.0 XML Schema (pub47.xsd).
 - The naming convention adopted for this new version, whereby the version number forms part of the name, will be used for future versions of the Pub 47 XML Schema.
 - ii The header of the XML document contains the version number to assist the receiving centres to properly ingest the metadata.
 - iii The XML metadata format is described at attachment 2.
 - iv The XML document structure is described at attachment 3.
- c. A new CSV format is required to accommodate recommendation 1 and 2:

- i The header of the CSV document contains the version number to assist the receiving centres to properly ingest the metadata.
 - ii The new CSV format is at attachment 4.
 - iii The CSV document structure is at attachment 5.
-

Attachment 1 (WMO-No. 47 changes)

Attachment 1

Pub 47 Code table 1601

prST Transmission system for sending weather reports.

	Code	Description
Costs borne by the ship	SVCE	Voice (ship). The observation is sent to a NMS through the telephone network. The communication may use Inmarsat, Iridium, Vsat, VHF
	SMAI	Email (ship). The observation is sent to a NMS through an email. The WMO message is attached to this email. The satellite communication provider may be Inmarsat, Iridium, Vsat
	SWEB	Web (ship). The observation is sent through the Web (example: TurboWeb). The satellite communication provider may be Inmarsat, Iridium, Vsat
Conventional VOS	CT41	Inmarsat-C (FM13, SAC41). Standard procedure used to report observations (FM13 messages) from conventional VOS for many years. Collect call system: the NMS which receives the observations pays the communication costs
	CTX	Inmarsat-C (FM13, other SAC). FM13 messages are sent to a dedicated SAC (other than SAC41) established at one, or more LES. In general, communications are paid by the country who recruited the ship
	CTH	Inmarsat-C (EUHC). Text messages containing compressed data (E-SURFMAR format) are sent ashore through Inmarsat-C to a dedicated SAC and LES. Communications are paid by the country who recruited the ship
	CDS	Inmarsat-C (SEAS). SEAS binary messages sent through Inmarsat-C Data Mode to a dedicated SAC and LES. Communications are paid by NOAA/NWS
Shipboard Automatic Weather Stations	AIS	Automated Identification System (direct or through satellite)
	ARG	Argos system
	TDUP	Cellular (Dial-up). Dial-up communication using terrestrial wireless networks (GSM, GPRS)
	TSMS	Cellular (SMS). SMS sent through terrestrial wireless networks (GSM, GPRS)
	GBS	Globalstar communication system
	GMS	GMS (DCP). Data Collecting Platform of Geostationary Meteorological Satellites
	ISBD	Iridium (SBD). Short Burst Data service of Iridium communication system
	IMAI	Iridium (Email). Email sent through Iridium (e.g. Easymail)
	IDUP	Iridium (Dial-up). Dial-up communication using Iridium
	CDM	Inmarsat-C (Data Mode). Data Mode service of Inmarsat-C used by S-AWS. See above for SEAS which also uses this service for conventional VOS
	CMAI	Inmarsat-C (Email). Email sent through Inmarsat-C
	ORBC	Orbcomm communication system
	VMAI	Vsat (Email). Email sent through Vsat
	VDUP	Vsat (Dial-up). Dial-up communication using Vsat
	OT	Other (specify in footnote).

Attachment 2 (WMO-No. 47 changes)

Attachment 2.

WMO-No. 47

Metadata Format Version 04

XML exchange format – element descriptions, formats and sequence

Order	Code Name	Header Code Name Explanation	Table	Format	Footnote*	Example
1	country	Recruiting country.	1801		No	
2	version	Metadata format version			No	04
3	prepared	Date of report preparation.		yyyymmdd	No	

Order	Code Name	Record Code Name Explanation	Table	Format	Footnote*	Example
1	nmsID	NMS reference number. Unique reference or identifier assigned by the NMS to the ship (if applicable).			No	
2	name	Ship's name.			No	
3	reg	Country of registration.	1801		No	
4	call	Call sign or WMO Number. Some sea stations are identified by a WMO Number instead of a call sign.			No	
5	IMOn	IMO Number. Unique identifying number assigned by Lloyd's Register to the hull of the ship.			No	
6	vssl	Vessel type.	2201		Yes	
7	vssIP	Vessel digital image.	2203		No	
8	lenvssID	Length overall of the ship, ignoring bulbous bow.		0.0 m	No	
9	brdvssID	Moulded breadth. The greatest breadth amidships.		0.0 m	No	
10	frbvssID	Freeboard. The average height of the upper deck above the maximum Summer load line.		0.0 m	No	
11	drfvssID	Draught. The average depth of the keel below the maximum Summer load line.		0.0 m	No	
12	chtvssID	Cargo height. Maximum height above the maximum Summer load line.		0.0 m	No	
13	brdg	Distance of the bridge from the bow.		0.0 m	No	
14	spd	Maximum operating speed of the vessel on normal service.		0 kts	No	
15	rie	Route No.1.	1802		Yes	
16	rie	Route No.2.	1802		Yes	
17	rie	Route No.3.	1802		Yes	
18	rie	Route No.4.	1802		Yes	

19	rie	Route No.5.	1802		Yes	
20	rie	Route No.6.	1802		Yes	
21	rie	Route No.7	1802		Yes	
22	rie	Route No.8.	1802		Yes	
23	rie	Route No.9.	1802		Yes	
24	rie	Route No.10.	1802		Yes	
25	vosR	Recruitment date of the current VOS participation.		yyyymmdd	No	
26	vosD	De-recruitment date of the last VOS participation (report only if the vessel has been re-recruited).		yyyymmdd	No	
27	vclmR	Last VOSclim recruitment date if within the current period of VOS participation.		yyyymmdd	No	
28	vclmD	Last VOSclim de-recruitment date if within the current period of VOS participation.		yyyymmdd	No	
29	vssIM	Type of meteorological reporting ship.	2202		Yes	
30	atm	General observing practice.	0105		Yes	
31	freq	Routine observing frequency.	0602		Yes	
32	prST	Transmission system for sending weather reports.	1601		Yes	
33	logE	Name and version of the electronic logbook software.			No	TurboWin 3.5
34	wwH	Visual wind/wave observing height.		0.0 m	No	
35	anmU	General wind observing practice.	0103		Yes	
36	blc	Baseline check of the automatic weather station.	0203		Yes	
37	awsM	Make and model of the automatic weather station.			No	Vaisala Mios 500
38	awsP	Name and version of the automatic weather station processing software.			No	Milos 500 2.56
39	awsC	Name and version of the automatic weather station data entry/display software.			No	Yourlink 1.03.20
40	barm	Primary barometer type.	0202		Yes	
41	bMS	Make and model of the primary barometer.			No	Vaisala PTB220B
42	brmH	Height of the primary barometer above the maximum Summer load line.		0.0 m	No	
43	brmL	Location of the primary barometer.	0204		Yes	
44	brmU	Pressure units of the primary barometer.			No	hPa
45	brmC	Most recent calibration date of the primary barometer.		yyyymmdd	No	
46	barm	Secondary barometer type.	0202		Yes	
47	bMS	Make and model of the secondary barometer.			No	
48	brmH	Height of the secondary barometer above the maximum Summer load line.		0.0 m	No	
49	brmL	Location of the secondary barometer.	0204		Yes	
50	brmU	Pressure units of the secondary barometer.			No	
51	brmC	Most recent calibration date of the secondary barometer.		yyyymmdd	No	

52	thrm	Dry bulb thermometer type No.1.	2002		Yes	Rosemount ST401
53	thMS	Make and model of the dry bulb thermometer No.1.			No	
54	thmE	Exposure of the dry bulb thermometer No.1.	0801		Yes	
55	thmL	Location of dry bulb thermometer No.1 and hygrometer No.1.	2001		Yes	
56	thmH	Height of the dry bulb thermometer No.1 and hygrometer No.1 above the maximum Summer load line.		0.0 m	No	
57	tscale	General reporting practice for dry bulb thermometer No.1 and hygrometer No.1.	2003		Yes	
58	thrm	Dry bulb thermometer type No.2.	2002		Yes	
59	thMS	Make and model of the dry bulb thermometer No.2.			No	
60	thmE	Exposure of the dry bulb thermometer No.2.	0801		Yes	
61	thmL	Location of dry bulb thermometer No.2 and hygrometer No.2.	2001		Yes	
62	thmH	Height of the dry bulb thermometer No.2 and hygrometer No.2 above the maximum Summer load line.		0.0 m	No	
63	tscale	General reporting practice for dry bulb thermometer No.2 and hygrometer No.2.	2003		Yes	
64	hygr	Hygrometer type No.1.	0802		Yes	
65	hgrE	Exposure of the hygrometer No.1.	0801		Yes	
66	hygr	Hygrometer type No.2.	0802		Yes	
67	hgrE	Exposure of the hygrometer No.2.	0801		Yes	
68	sstM	Primary method of obtaining the sea surface temperature.	1901		Yes	
69	sstD	Depth of the primary sea surface temperature observation below the maximum Summer load line.		0.0 m	No	
70	sstM	Secondary method of obtaining the sea surface temperature.	1901		Yes	
71	sstD	Depth of the secondary sea surface temperature observation below the maximum Summer load line.		0.0 m	No	
72	barg	Primary barograph type, or method of determining pressure tendency.	0201		Yes	
73	barg	Secondary barograph type, or method of determining pressure tendency.	0201		Yes	
74	anmT	Primary anemometer type.	0102		Yes	Vaisala WAV151 & WAA151
75	anmM	Make and model of the primary anemometer.			No	
76	anmL	Location of the primary anemometer.	0101		Yes	
77	anDB	Distance of the primary (fixed) anemometer from the bow.		0.0 m	No	
78	anDC	Distance of the primary (fixed) anemometer from the centre line.		0.0 m	No	
79	anSC	Side indicator of the primary (fixed) anemometer from the centre line, if appropriate.	0104		No	
80	anHL	Height of the primary (fixed) anemometer above the maximum Summer load line.		0.0 m	No	
81	anHD	Height of the primary (fixed) anemometer above the deck on which it is installed.		0.0 m	No	
82	anmC	Most recent calibration date of the primary anemometer.		yyymmdd	No	
83	anmT	Secondary anemometer type.	0102		Yes	

84	anmM	Make and model of the secondary anemometer.			No	
85	anmL	Location of the secondary anemometer.	0101		Yes	
86	anDB	Distance of the secondary (fixed) anemometer from the bow.		0.0 m	No	
87	anDC	Distance of the secondary (fixed) anemometer from the centre line.		0.0 m	No	
88	anSC	Side indicator of the secondary (fixed) anemometer from the centre line, if appropriate.	0104		No	
89	anHL	Height of the secondary (fixed) anemometer above the maximum Summer load line.		0.0 m	No	
90	anHD	Height of the secondary (fixed) anemometer above the deck on which it is installed.		0.0 m	No	
91	anmC	Most recent calibration date of the secondary anemometer.		yyyymmdd	No	
92	oth1	Other meteorological/oceanographic instrument No.1.	1501		Yes	
93	oth1	Other meteorological/oceanographic instrument No.2.	1501		Yes	
94	oth1	Other meteorological/oceanographic instrument No.3.	1501		Yes	
95	oth1	Other meteorological/oceanographic instrument No.4.	1501		Yes	
96	oth1	Other meteorological/oceanographic instrument No.5.	1501		Yes	
97	oth1	Other meteorological/oceanographic instrument No.6.	1501		Yes	
98	chgd	Last date of change to any metadata value.		yyyymmdd	No	

* Provision to report a footnote (Mandatory extra detail if OT is selected from a Code Table. Optional if Yes in footnote column)

Attachment 3 (WMO-No. 47 changes)

Attachment 3.

WMO-No. 47

Metadata Format Version 04

XML File Structure and element sequence

Important changes from version 03 are highlighted

```

<?xml version="1.0"?>
<pub47dataset country="" version="04" prepared="" namespace>
  <pub47record nmsID="">
    <name>
      <reg>
      <call>
      <IMOn>
      <vssl footnote=""/>
      <digital_image>
        <vsslP/>
      </digital_image>
      <dimensions>
        <lenvsslD/>
        <brdvsslD/>
        <frbvsslD/>
        <drfvsslD/>
        <chrvsslD/>
        <brdg>
        <spd>
      </dimensions>
      <operations>
        <rtb id="1" footnote=""/>
        <rtb id="2" footnote=""/>
        <rtb id="3" footnote=""/>
        <rtb id="4" footnote=""/>
        <rtb id="5" footnote=""/>
        <rtb id="6" footnote=""/>
      </operations>
    </pub47record>
  </pub47dataset>

```

<< New version number, namespace specification at end of attachment 3.

<< New element added in version 04.

```

        <rtb Id="7" footnote="" />
        <rtb Id="8" footnote="" />
        <rtb Id="9" footnote="" />
        <rtb Id="10" footnote="" />
    </operations>
    <vos_service>
        <vosR />
        <vosD />
        <vclmR />
        <vclmD />
    </vos_service>
    <met_prgm>
        <vssIM footnote="" />
        <atm footnote="" />
        <freq footnote="" />
        <prST footnote="" />
        <logE />
        <wwH />
        <anmU footnote="" />
        <bic footnote="" />
    </met_prgm>
    <instrumentation>
        <automated Id="1">
            <awsM />
            <awsP />
            <awsC />
        </automated>
        <barometer Id="1">
            <barm footnote="" />
            <bMS />
            <brmH />
            <brmL footnote="" />
            <brmU />
            <brmC />
        </barometer>
        <barometer Id="2">
            <barm footnote="" />
            <bMS />
            <brmH />
            <brmL footnote="" />
            <brmU />
            <brmC />
        </barometer>
    </instrumentation>

```

<< Footnote added to element prST in version 04.

```

<dry_bulb id="1">
  <thrm footnote=""/>
  <thMS/>
  <thmE footnote=""/>
  <thmL footnote=""/>
  <thmH/>
  <tscall footnote=""/>
</dry_bulb>
<dry_bulb id="2">
  <thrm footnote=""/>
  <thMS/>
  <thmE footnote=""/>
  <thmL footnote=""/>
  <thmH/>
  <tscall footnote=""/>
</dry_bulb>
<hygrometer id="1">
  <hygr footnote=""/>
  <hygE footnote=""/>
</hygrometer>
<hygrometer id="2">
  <hygr footnote=""/>
  <hygE footnote=""/>
</hygrometer>
<sea_temp id="1">
  <sstM footnote=""/>
  <sstD/>
</sea_temp>
<sea_temp id="2">
  <sstM footnote=""/>
  <sstD/>
</sea_temp>
<barograph id="1">
  <barg footnote=""/>
</barograph>
<barograph id="2">
  <barg footnote=""/>
</barograph>

```

```

    <anemometer id="1">
      <anmT footnote=""/>
      <anmM/>
      <anmL footnote=""/>
      <anDB/>
      <anDC/>
      <anSC/>
      <anHL/>
      <anHD/>
      <anmC/>
    </anemometer>
    <anemometer id="2">
      <anmT footnote=""/>
      <anmM/>
      <anmL footnote=""/>
      <anDB/>
      <anDC/>
      <anSC/>
      <anHL/>
      <anHD/>
      <anmC/>
    </anemometer>
    <other>
      <othl id="1" footnote=""/>
      <othl id="2" footnote=""/>
      <othl id="3" footnote=""/>
      <othl id="4" footnote=""/>
      <othl id="5" footnote=""/>
      <othl id="6" footnote=""/>
    </other>
  </instrumentation>
</chgd>
</pub47record>
</pub47dataset>

```

namespace specification for Pub47 XML Schema, version 4.0:

xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="http://www.bom.gov.au/jcomm/vos/pub47/v4pub47.xsd"

Attachment 4 (WMO-No. 47 changes)

Attachment 4

WMO-No. 47

Metadata Format Version 04

Semi-colon delimited exchange format – element descriptions, formats and sequence

Order	Code Name	Explanation	Table	Format	Footnote	Example
1	rcnty;	Recruiting country.	1801		No	
2	ver;	Metadata format version			No	04
3	prepared;	Date of report preparation.		ddmmyyyy	No	
4	name;	Ship's name.			No	
5	reg;	Country of registration.	1801		No	
6	call;	Call sign or WMO Number. Some sea stations are identified by a WMO Number instead of a call sign.			No	
7	IMOn;	IMO Number. Unique identifying number assigned by Lloyd's Register to the hull of the ship.			No	
8	vssl;	Vessel type.	2201		Yes	
9	vssIP;	Vessel digital image.	2203		No	
10	lenvssID;	Length overall of the ship, ignoring bulbous bow.		0.0 m	No	
11	brdvssID;	Moulded breadth. The greatest breadth amidships.		0.0 m	No	
12	frtvssID;	Freeboard. The average height of the upper deck above the maximum Summer load line.		0.0 m	No	
13	drfvssID;	Draught. The average depth of the keel below the maximum Summer load line.		0.0 m	No	
14	chtvssID;	Cargo height. Maximum height above the maximum Summer load line.		0.0 m	No	
15	brdg;	Distance of the bridge from the bow.		0.0 m	No	
16	spd;	Maximum operating speed of the vessel on normal service.		0 kts	No	
17	rie;	Route No.1.	1802		Yes	
18	rie;	Route No.2.	1802		Yes	
19	rie;	Route No.3.	1802		Yes	
20	rie;	Route No.4.	1802		Yes	
21	rie;	Route No.5.	1802		Yes	
22	rie;	Route No.6.	1802		Yes	
23	rie;	Route No.7	1802		Yes	

24	rie;	Route No.8.	1802		Yes	
25	rie;	Route No.9.	1802		Yes	
26	rie;	Route No.10.	1802		Yes	
27	vosR;	Recruitment date of the current VOS participation.		ddmmyyyy	No	
28	vosD;	De-recruitment date of the last VOS participation (report only if the vessel has been re-recruited).		ddmmyyyy	No	
29	vclmR;	Last VOSCLim recruitment date if within the current period of VOS participation.		ddmmyyyy	No	
30	vclmD;	Last VOSCLim de-recruitment date if within the current period of VOS participation.		ddmmyyyy	No	
31	vssIM;	Type of meteorological reporting ship.	2202		Yes	
32	atm;	General observing practice.	0105		Yes	
33	freq;	Routine observing frequency.	0602		Yes	
34	prST;	Transmission system for sending weather reports.	1601		Yes	
35	logE;	Name and version of the electronic logbook software.			No	TurboWin 3.5
36	wwH;	Visual wind/wave observing height.		0.0 m	No	
37	anmU;	General wind observing practice.	0103		No	
38	blc;	Baseline check of the automatic weather station.	0203		No	
39	awsM;	Make and model of the automatic weather station.			No	Vaisala Milos 500
40	awsP;	Name and version of the automatic weather station processing software.			No	Milos 500 2.56
41	awsC;	Name and version of the automatic weather station data entry/display software.			No	Yourlink 1.03.20
42	barm;	Primary barometer type.	0202		Yes	
43	barm;	Secondary barometer type.	0202		Yes	
44	bMS;	Make and model of the primary barometer.			No	Vaisala PTB220B
45	bMS;	Make and model of the secondary barometer.			No	
46	brmH;	Height of the primary barometer above the maximum Summer load line.		0.0 m	No	
47	brmH;	Height of the secondary barometer above the maximum Summer load line.		0.0 m	No	
48	brmL;	Location of the primary barometer.	0204		Yes	
49	brmL;	Location of the secondary barometer.	0204		Yes	
50	brmU;	Pressure units of the primary barometer.			No	hPa
51	brmU;	Pressure units of the secondary barometer.			No	
52	brmC;	Most recent calibration date of the primary barometer.		ddmmyyyy	No	
53	brmC;	Most recent calibration date of the secondary barometer.		ddmmyyyy	No	
54	thrm;	Dry bulb thermometer type No.1.	2002		Yes	
55	thrm;	Dry bulb thermometer type No.2.	2002		Yes	
56	thMS;	Make and model of the dry bulb thermometer No.1.			No	Rosemount ST401

57	thmS;	Make and model of the dry bulb thermometer No.2.			No	
58	thmE;	Exposure of the dry bulb thermometer No.1.	0801		Yes	
59	thmE;	Exposure of the dry bulb thermometer No.2.	0801		Yes	
60	thmL;	Location of dry bulb thermometer No.1 and hygrometer No.1.	2001		Yes	
61	thmL;	Location of dry bulb thermometer No.2 and hygrometer No.2.	2001		Yes	
62	thmH;	Height of the dry bulb thermometer No.1 and hygrometer No.1 above the maximum Summer load line.		0.0 m	No	
63	thmH;	Height of the dry bulb thermometer No.2 and hygrometer No.2 above the maximum Summer load line.		0.0 m	No	
64	tscalc;	General reporting practice for dry bulb thermometer No.1 and hygrometer No.1.	2003		Yes	
65	tscalc;	General reporting practice for dry bulb thermometer No.2 and hygrometer No.2.	2003		Yes	
66	hygr;	Hygrometer type No.1.	0802		Yes	
67	hygr;	Hygrometer type No.2.	0802		Yes	
68	hgrE;	Exposure of the hygrometer No.1.	0801		No	
69	hgrE;	Exposure of the hygrometer No.2.	0801		No	
70	sstm;	Primary method of obtaining the sea surface temperature.	1901		Yes	
71	sstm;	Secondary method of obtaining the sea surface temperature.	1901		Yes	
72	sstD;	Depth of the primary sea surface temperature observation below the maximum Summer load line.		0.0 m	No	
73	sstD;	Depth of the secondary sea surface temperature observation below the maximum Summer load line.		0.0 m	No	
74	barg;	Primary barograph type, or method of determining pressure tendency.	0201		Yes	
75	barg;	Secondary barograph type, or method of determining pressure tendency.	0201		Yes	
76	anmT;	Primary anemometer type.	0102		Yes	
77	anmT;	Secondary anemometer type.	0102		Yes	
78	anmM;	Make and model of the primary anemometer.			No	Vaisala WAV151 & WAA151
79	anmM;	Make and model of the secondary anemometer.			No	
80	anmL;	Location of the primary anemometer.	0101		Yes	
81	anmL;	Location of the secondary anemometer.	0101		Yes	
82	anDB;	Distance of the primary (fixed) anemometer from the bow.		0.0 m	No	
83	anDB;	Distance of the secondary (fixed) anemometer from the bow.		0.0 m	No	
84	anDC;	Distance of the primary (fixed) anemometer from the centre line.		0.0 m	No	
85	anSC;	Side indicator of the primary (fixed) anemometer from the centre line, if appropriate.	0104		No	
86	anDC;	Distance of the secondary (fixed) anemometer from the centre line.		0.0 m	No	
87	anSC;	Side indicator of the secondary (fixed) anemometer from the centre line, if appropriate.	0104		No	
88	anHL;	Height of the primary (fixed) anemometer above the maximum Summer load line.		0.0 m	No	

89	anHL;	Height of the secondary (fixed) anemometer above the maximum Summer load line.		0.0 m	No	
90	anHD;	Height of the primary (fixed) anemometer above the deck on which it is installed.		0.0 m	No	
91	anHD;	Height of the secondary (fixed) anemometer above the deck on which it is installed.		0.0 m	No	
92	anmC;	Most recent calibration date of the primary anemometer.		ddmmyyyy	No	
93	anmC;	Most recent calibration date of the secondary anemometer.		ddmmyyyy	No	
94	othI;	Other meteorological/oceanographic instrument No.1.	1501		Yes	
95	othI;	Other meteorological/oceanographic instrument No.2.	1501		Yes	
96	othI;	Other meteorological/oceanographic instrument No.3.	1501		Yes	
97	othI;	Other meteorological/oceanographic instrument No.4.	1501		Yes	
98	othI;	Other meteorological/oceanographic instrument No.5.	1501		Yes	
99	othI;	Other meteorological/oceanographic instrument No.6.	1501		Yes	
100	chgd;	Last date of change to any metadata value.		ddmmyyyy	No	
101	fieldabbrev;	Code name of the field to which footnote No. 1 applies.	0601			vsl thmE rte
102	fieldabbrev;	Code name of the field to which footnote No. 2 applies.	0601			
103	fieldabbrev;	Code name of the field to which footnote No. 3 applies.	0601			
104	fieldabbrev;	Code name of the field to which footnote No. 4 applies.	0601			
105	fieldabbrev;	Code name of the field to which footnote No. 5 applies.	0601			
106	fieldabbrev;	Code name of the field to which footnote No. 6 applies.	0601			
107	fieldabbrev;	Code name of the field to which footnote No. 7 applies.	0601			
108	fieldabbrev;	Code name of the field to which footnote No. 8 applies.	0601			
109	fieldabbrev;	Code name of the field to which footnote No. 9 applies.	0601			
110	fieldabbrev;	Code name of the field to which footnote No. 10 applies.	0601			
111	footID;	Footnote No. 1 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				Ice strengthened Plastic screen Area 73 – Austral Summer only
112	footID;	Footnote No. 2 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
113	footID;	Footnote No. 3 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
114	footID;	Footnote No. 4 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
115	footID;	Footnote No. 5 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
116	footID;	Footnote No. 6 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
117	footID;	Footnote No. 7 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
118	footID;	Footnote No. 8 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
119	footID;	Footnote No. 9 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				
120	footID;	Footnote No. 10 (Mandatory extra details if code OT is reported. Optional if Yes in footnote column)				

WMO-No. 47

Metadata Format Version 04

CSV File Structure and element sequence

Important changes from version 03 are highlighted

[illegible]

Notes:

1. Each metadata element is separated from the next metadata element by a semi-colon delimiter.
2. All metadata elements are reported on one line of text.